



# LU300W



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

Luminator sensor with two weatherproof, corrosionproof floodlights and round mounting plate. PRE-WIRED FOR EASY INSTALLATION. Both floods and sensor have universal ball swivels for easy tool-less adjustment. Lamps not supplied.

## SPECIFICATIONS

### UL Listing

Suitable for wet locations.

### Voltage

120 volts AC 60 Hz.

### Power Consumption

1 watt

### Time Adjustment

8 seconds to 10 minutes

### Photo Control

Deactivates lights during daylight

### Detector Sensitivity

Adjustable from 100% to 50%

### Wall Switch Manual Override

Two flip logic prevents activation by momentary power outages. Override resets to auto after 6 hours or at dawn. No extra wiring needed.

### Auto Test Logic

5 minutes of test time when power is turned on, Rests to auto mode without further adjustment

### Sensor Housing

Made of tough, corrosion resistant polycarbonate

### Floodlights

Made of tough, corrosion-resistant polycarbonate. Accepts PAR-38 lamps, medium base, 150 watts max. Lamps not included.

### Surge Protection

Withstands up to 3000 volts

### Detection

110° view

### Switching Capacity

300 watts incandescent @ 120 volts, 2.5 amps

### Patents

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

### Color

White

### Weight

1.24

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com

© 2011