


PANEL2X2-34Y

LED panel lights are an easy way to dramatically drop energy consumption in office spaces, reducing wattage by 31 - 64%, and utility rebates are readily available of up to \$100 per fixture.

Color: Gloss white

Weight: 21.0 lbs



LED Info

Watts: 34W
 Color Temp: 3000K
 Color Accuracy: 85
 L70 Lifespan: 100000
 LM79 Lumens: 2,635
 Efficacy: 78 LPW

Driver Info

Type: N/A
 120V: 0.29A
 208V: 0.167A
 240V: 0.145A
 277V: 0.126A
 Input Watts: 34W
 Efficiency: 101%

Technical Specifications

UL Listed:

Suitable for damp locations.

IC Rating:

Suitable for insulated ceilings.

Lumen Maintenance:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

Long-life, High efficiency, micro-power, surface mount LEDs; binned and mixed for uniform light output and color.

Driver:

Constant Current, Class 2, 100-277V, 50/60Hz, 4kV Surge Protection, 700mA, 100-277V 0.4A, THD $\leq 8.8\%$; 20%, Power factor 97.9%.

Lens:

High-transmission acrylic lens with excellent distribution and uniformity.

Correlated Color Temp. (Nominal CCT):

3000K.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Housing:

Lightweight housing is constructed of extruded aluminum.

Fixture Efficacy:

78 Lumens per Watt.

Color Accuracy (CRI):

85 CRI.

Finish:

High-reflectance (91%) powder coat applied post production for a more durable finish.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24:

PANELS complies with California Title 24 building and electrical codes.

Quick and Easy Installation:

Modular splice box/driver compartment available for quick installation. Integral Tee grid clips make installation easy and secure.

Green Technology:

Mercury and UV free, and RoHS compliant.

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. See our full warranty .

