PANEL2X2-41Y

LED panel lights are an easy way to dramatically drop energy consumption in office spaces, reducing wattage by 31 - 64%, and utility rebates are readily available of up to \$100 per fixture.

LED Info		Driver Info	
Watts:	41W	Type:	N/A
Color Temp:	3000K	120V:	0.33A
Color Accuracy:	85	208V:	0.202A
L70 Lifespan:	100000	240V:	0.175A
LM79 Lumens:	2,877	277V:	0.152A
Efficacy:	76 LPW	Input Watts:	38W
		Efficiency:	108%

Color: Gloss white Weight: 21.0 lbs

Technical Specifications

UL Listed:

Suitable for damp locations.

IC Rating:

Suitable for insulated ceilings.

Lumen Maintenance:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

Long-life, High efficiency, micro-power, surface mount LEDs; binned and mixed for uniform light output and color.

Driver:

Constant Current, Class 2, 100-277V, 50/60Hz, 4KV Surge Protection, 800mA, THD≤ 20%, Power factor 99.4%.

Lens:

High-transmission acrylic lens with excellent distribution and uniformity.

Correlated Color Temp. (Nominal CCT):

3000K.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Housing:

Lightweight housing is constructed of extruded aluminum.

Color Accuracy (CRI):

85 CRI.

Finish:

High-reflectance (91%) powder coat applied post production for a more durable finish.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24:

PANELS complies with California Title 24 building and electrical codes.

Quick and Easy Installation:

Modular splice box/driver compartment available for quick installation. Integral Tee grid clips make installation easy and secure.

Green Technology:

Mercury and UV free, and RoHS compliant.

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. See our full warranty.

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.



Email: sales@rabweb.com

On the web at: www.rabweb.com

Note: Specifications are subject to change without notice

PANEL2X2-41Y - continued

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods--Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

