


QF200FW

The Mini Curve. High quality die cast flood with rounded back and integral glare shield. Tempered glass lens. Gold plated socket contacts and 250 deg. C Teflon coated wires for extended lamp life. 200 watt double ended 130 volt Quartz halogen lamp supplied.

Color: White

Weight: 1.8 lbs



Lamp Info

Type: T3
 Watts: 200W
 Shape/Size: N/A
 Base: N/A
 ANSI: N/A
 Hours: 2,000
 Lamp Lumens: 3,600
 Efficacy: 18 LPW

Ballast Info

Type: 0
 120V: N/A
 208V: 0
 240V: N/A
 277V: N/A
 Input Watts: 200W
 Efficiency: 100%

Technical Specifications

UL Listing:

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground

Housing:

Die cast aluminum, 1/2" NPS threaded arm with locking swivel fits all standard mounting covers.

Lens Gasket:

High temperature silicone gasket stays in place during relamping

Reflector:

Semi-specular anodized aluminum

Sockets:

Porcelain RSC base sockets with gold plated spring loaded contacts and strain relieved 250° C Teflon insulated wires

Lens:

Thermal, tempered, shock resistant glass

Finish:

Chip and fade resistant polyester powder coating

Patents:

The unique RAB Quartz Curve is protected by U.S. Patent D565,223; China Patent ZL200730149209.5; Taiwan Patent D124,862 and Canada Patent D121,992

