



JOB NAME:	
DATE:	
TYPE:	

# DESCRIPTION

STEALTH 110 Sensor with twin precision die cast H101 Deluxe shielded floods pre-wired and assembled on universal CU4 cover plate.

## **SPECIFICATIONS**

#### **UL Listing**

Suitable for wet locations

## **Power Consumption**

1 watt

#### **Time Adjustment**

5 seconds to 12 minutes

# **Surge Protection**

Withstands up to 6000 volts

## **Wide Sensitivity Control**

Adjustable from 100% to 30%

## **Temperature Compensation**

Sensitivity adjusts automatically for consistent detection in hot and cold ambient temperatures

## **Wall Switch Manual Override**

Two flip logic prevents activation by momentary power outages. Override resets to auto at dawn. No extra wiring needed

## **LED Detection Indicator**

Shows when sensor is detecting in daytime and glows red at night for "on-guard" deterrence

### **Advanced Detection Logic**

Minimizes false triggers

#### **Color Matched Lens**

Dark lens with bronze units, white lens with white units

## **RF Immunity**

Circuits fully shielded for maximum radio frequency immunity

#### Horizontal Lock, No-tool Joints

Keeps sensing pattern level for fast, error-free installation

#### **Photoelectric Control**

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications

#### **Floodlights**

Precision die cast aluminum. 1/2" NPS threaded arm with serrated locking swivel fits all standard mounting boxes and covers

#### Lamp

Accepts PAR38 lamps, 150 watt max. Lamps are not supplied.

#### Voltage

120 Volts AC 60 Hertz

#### **Lens Mask**

Customized press apply lens mask included to reduce coverage easily

#### **Detection**

200• view

## **Switching Capacity**

1000 watts incandescent @ 120 volts, 8 amps

#### **Patents**

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

## Warranty

10 year sensor warranty


#### Color

Bronze


## Weight

5

## **DIMENSIONS**



# **DETECTION PATTERN**



JU