

Product 14010

Number:

Order 45PAR38/HAL/WFL50 130V

Abbreviation:

General Tungsten Halogen CAPSYLITE PAR38 Reflector Lamp Medium Skirt

Description: Base 45Watt 130Volt Wide Flood Beam

Product Information	
Abbrev. With Packaging Info.	45PAR38HALWFL50 130V 15/CS 1/SKU
Approx. Lumens	560
Average Rated Life (hr)	2500
Base	E26 Medium Skirted
Beam Angle (deg)	50
Beam Type	WFL
Bulb	PAR38
Centerbeam Candlepower (cp)	700
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2825
Diameter (in)	4.752
Diameter (mm)	120.70
Ecologic	YES
Family Brand Name	CAPSYLITE® PAR38 SPL
Filament	CC-8
Horizontal Beam Angle (deg)	50
Lamp Finish	Reflector
Maximum Overall Length - MOL (in)	5.313
Maximum Overall Length - MOL (mm)	134.9375
Nominal Voltage (V)	130.00
Nominal Wattage (W)	45.00
Vertical Beam Angle (deg)	50







Footnotes

- State of the Art SPL Optics
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.

1 of 2 9/20/2011 1:15 PM

- Approximate life for 130 volt tungsten halogen lamps operated at 120 volts is within the value calculated using the recommended equations
 for standard incandescent lamps, as set forth in the IES Handbook, 8th edition. Because of the uncertain nature of the halogen cycle on the
 coil when operated at less than rated voltage, life of tungsten halogen lamps varies considerably and unpredictably. OSRAM SYLVANIA
 does not recommend operation at other than rated voltage.
- @ 120 volts, approximate 40 watts, 425 lumens, 5000 hours

2 of 2 9/20/2011 1:15 PM