Return to search



Print Page

Product Number: Order Abbreviation: General Description: 14533

50PAR30/HAL/FL40 130V

Tungsten Halogen CAPSYLITE PAR30 Reflector Lamp Medium Base 50Watt 130Volt Flood Beam

Product Information	
Abbrev. With Packaging Info.	50PAR30HALFL40 130V 15/CS 1/SKU
Approx. Lumens	660
Average Rated Life (hr)	2500
Base	E26 Medium
Beam Angle (deg)	40
Beam Type	FL
Bulb	PAR30
Centerbeam Candlepower (cp)	1300
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2850
Diameter (in)	3.75
Diameter (mm)	95.25
Ecologic	YES
Family Brand Name	CAPSYLITE® PAR30 SPL
Filament	CC-8
Horizontal Beam Angle (deg)	40
Maximum Overall Length - MOL (in)	3.625
Maximum Overall Length - MOL (mm)	92.075
Nominal Voltage (V)	130.00
Nominal Wattage (W)	50.00
Vertical Beam Angle (deg)	40

Additional Product Information <u>Product Documents, Graphs, and Images</u>

Packaging Information





Footnotes

- State of the Art SPL Optics
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.
- Approximate life for 130 volt tungsten halogen lamps operated at 120 volts is within the value calculated using the recommended equations for standard incandescent lamps, as set forth in the IES Handbook, 8th edition. Because of the uncertain nature of the halogen cycle on the coil when operated at less than rated voltage, life of tungsten halogen lamps varies considerably and unpredictably. OSRAM SYLVANIA does not recommend operation at other than rated voltage.
- @ 120 volts, approximate 44 watts, 500 lumens, 5000 hours

Print Page