Product Details Page 1 of 2

Return to search



Print Page

Product

15558

Number: Order

250PAR38/HAL/FL30 120V

Abbreviation: General Description:

Tungsten Halogen CAPSYLITE PAR38

Reflector Lamp Medium Skirted Base 250Watt

120Volt Flood Beam

Product Information

Abbrev. With Packaging Info. 250PAR38HALFL30 120V 6/CS 1/SKU

Approx. Lumens 3600 Average Rated Life (hr) 4500

Base E26 Medium Skirted

Beam Angle (deg) 30 Beam Type FL PAR38 Bulb Centerbeam Candlepower (cp) 9000 Class C (gas) Color Rendering Index (CRI) 100 Color Temperature/CCT (K) 3025 Diameter (in) 4.75 Diameter (mm) 120.65

Family Brand Name CAPSYLITE® PAR38 SPL

Filament CC-8
Horizontal Beam Angle (deg) 30
Maximum Overall Length - MOL (in) 5.313
Maximum Overall Length - MOL (mm) 134.9375
Nominal Voltage (V) 120.00
Nominal Wattage (W) 250.00
Vertical Beam Angle (deg) 30

Additional Product Information


YES

Product Documents, Graphs, and Images

Packaging Information

Ecologic

Product Details Page 2 of 2



Footnotes

- State of the Art SPL Optics
- Because this bulb radiates considerable heat, do not use in enclosed, close fitting
 fixtures, or in close proximity to people, combustible materials, or substances adversely
 affected by heat or drying.
- Even though this bulb may continue to light after the lens or reflector is cracked or broken, it should be replaced as soon as possible since the pressure filled inner capsule could unexpectedly shatter, creating a risk of personal injury or property damage. In addition, the inner capsule produces ultraviolet radiation that can cause injury to the eyes and skin with prolonged exposure without the blocking effect of the outer glass bulb.
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- For indoor or outdoor use where not directly exposed to weather. Exposure to weather may damage the bulb.
- Use only with ceramic/porcelain sockets and in fixtures rated for this bulb type, including voltage and wattage.

Print Page