Return to search	Print Page	
	Product Number:	20317
	Order Abbreviation:	CF9DS/E/841
	General Description:	DULUX 5W single compact fluorescent lamp with 4-pin base, 2700K color temperature, 82 CRI, for use with electronic and dimming ballasts
Product Infor	mation	

Product Information		
Abbrev. With Packaging Info. C	CF9DSE841 50/CS 1/SKU	
Average Rated Life (hr) 1	10000	
Base 2	2G7	
Bulb S	5 (T4)	
Color Rendering Index (CRI) 8	32	
Color Temperature/CCT (K) 4	\$100	
Family Brand Name D	Dulux® S/E	
Industry Standards II	EC 60901- 2009	
Mean Lumens at 25C 4	199	
Maximum Overall Length - MOL (in) 5	5.7	
Maximum Overall Length - MOL (mm) 1	145	
Nominal Wattage (W) 9	9.00	

Additional Product Information

Product Documents, Graphs, and Images

Packaging Information



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal endof-life phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased,

- there will be a corresponding increase in the average hours life. Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar • light output.

Print Page