Product Details Page 1 of 2

Return to search

SYLVANIA

Print Page

Product Number: 29415

Order Abbreviation:

CF30EL/TWIST/2700K

General
Description:

DULUX EL 30W spiral compact fluorescent lamp, integral 120V ballast, medium screwbase, Color temperature 2700K, 82

CRI, packaged 6/carton

Product Information

Abbrev. With Packaging Info. CF30ELTWIST2700K 6/CS 1/SKU

Average Rated Life (hr) 10000
Base Medium
Bulb TWIST
Color Rendering Index (CRI) 82
Color Temperature/CCT (K) 2700
Diameter (in) 2.5

Diameter (in) 2,5
Diameter (mm) 63.5

Family Brand Name Dulux® EL

Industry Standards ANSI C78.5-2003

Initial Lumens at 25C 2000

Mean Lumens at 25C 1600

Maximum Overall Length - MOL (in) 5.13

Maximum Overall Length - MOL (mm) 130.3

Nominal Wattage (W) 30.00

Additional Product Information

Product Documents, Graphs, and Images

Packaging Information



Footnotes

Approximate initial lumens after 100 hours operation.

Product Details Page 2 of 2

 Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature.

- DULUX Els meet CSA, FCC and UL requirements.
- Caution: DULUX EL units cannot be used on dimming circuits (unless the lamp is labeled dimmable), emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature for DULUX EL lamps is 0 degrees F
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

Print Page