



Product Number: 54252

Order Abbreviation: 64638 HLX

General Description: 100 Watt, tungsten Halogen, low voltage without reflector

Product Information

Abbrev. With Packaging Info.	64638HLX 24V 40/CS 1/SKU
Application	Projector
Average Rated Life (hr)	300
Base	G6.35 Bipin
Bulb	T3
Class	C (gas)
Color Rendering Index (CRI)	100
Diameter d (in)	0.507
Diameter d (mm)	13.00
Distance a (in)	1.170
Distance a (mm)	30
Family Brand Name	XENOPHOT® (HLX)
Filament	C Bar 6
Filament Dimensions Length (in)	0.101
Filament Dimensions Length (mm)	2.6
Filament Dimensions Width (in)	0.207
Filament Dimensions Width (mm)	5.3
Lamp Finish	Clear
Length l (in)	1.950
Length l (mm)	50
Length l max. (in)	1.950
Length l max. (mm)	50
Light Center Length - LCL (in)	1.170
Light Center Length - LCL (mm)	30
Luminous Flux (lm)	2900
Maximum Overall Length - MOL (in)	1.950
Maximum Overall Length - MOL (mm)	50
Nominal Voltage (V)	24.00
Nominal Wattage (W)	100.00
Operating Position	Any
Reflector Coating	0009
Type of Current	AC