



Product Number: 54605

Order Abbreviation: HPL 750/120 (UCF)

General Description: 750 watt, tungsten halogen, HPL series

Product Information	
Abbrev. With Packaging Info.	HPL750120 (UCF) 120V 12/CS 1/SKU
Application	Stage & Studio
Average Rated Life (hr)	300
Base	Medium Bipin with Heat Sink
Bulb	T6
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3250
Diameter d (in)	0.748
Diameter d (mm)	19.00
Distance a (in)	2.352
Distance a (mm)	60.3
Family Brand Name	HPL
Filament	4-C8
Length l (in)	4.1
Length l (mm)	104
Length l max. (in)	4.1
Length l max. (mm)	104
Light Center Length - LCL (in)	2.352
Light Center Length - LCL (mm)	60.3
Luminous Flux (lm)	21900
Maximum Overall Length - MOL (in)	4.1
Maximum Overall Length - MOL (mm)	104
Nominal Voltage (V)	120.00
Nominal Wattage (W)	750.00
Operating Position	Any
Reflector Coating	19.00
Type of Current	AC

Footnotes

- High-performance HPL halogen lamps are manufactured under license from ETC, Inc.