

[Return to search](#)[Print Page](#)

Product Number: 64321
Order Abbreviation: M400/PS/U
General Description: 400W METALARC PULSE START metal halide lamp, reduced color shift, E39 base, BT37 bulb, enclosed fixture rated, universal burn, clear, 4000K

Product Information

Abbrev. With Packaging Info.	M400PSU 6/CS 1/SKU
ANSI Code	M155/E
ANSI Code 2	M135/O
Approx. Lumens (initial - horizontal)	31000
Approx. Lumens (initial - vertical)	36000
Approx. Lumens (mean - horizontal)	22400
Approx. Lumens (mean - vertical)	25500
Arc Length (in)	1.5
Arc Length (mm)	38
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	BT37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.6
Diameter (mm)	117
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292

Nominal Wattage (W)	400.00
Operating Position	Universal
Warm-up Time (min)	2-4

Additional Product Information
<u>Product Documents, Graphs, and Images</u>
<u>Packaging Information</u>

[Print Page](#)