

[Return to search](#)[Print Page](#)

**Product Number:** 64480  
**Order Abbreviation:** M175/C/U/MED  
**General Description:** Compact 175W reduced outer jacket, universal burn metal halide lamp, coated

#### Product Information

Abbrev. With Packaging Info.	M175CUMED 20/CS 1/SKU
ANSI Code	M57/E
Approx. Lumens (initial - horizontal)	11080
Approx. Lumens (initial - vertical)	13000
Approx. Lumens (mean - horizontal)	8400
Approx. Lumens (mean - vertical)	8400
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3600
Diameter (in)	2.13
Diameter (mm)	54
Family Brand Name	Compact Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7-12
Lamp Finish	Coated
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	132.00
Nominal Wattage (W)	175.00
Operating Position	Universal
Warm-up Time (min)	2-4
Average Rated Life - (hr)	7500

**Additional Product Information****Product Documents, Graphs, and Images****Compatible Ballast****Packaging Information****Footnotes**

- = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.

**| Print Page |**