

[Return to search](#)[Print Page](#)

**Product Number:** 64488

**Order Abbreviation:** M400/U/BT28

**General Description:** 400W METALARC compact quartz metal halide lamp, reduced outer jacket, E39 base, BT28 bulb, enclosed fixture rated, universal burn, clear, 4000K

#### Product Information

Abbrev. With Packaging Info.	M400UBT28 6/CS 1/SKU
ANSI Code	M59/E
Approx. Lumens (initial - horizontal)	32000
Approx. Lumens (initial - vertical)	36000
Approx. Lumens (mean - horizontal)	20500
Approx. Lumens (mean - vertical)	23500
Arc Length (in)	1.77
Arc Length (mm)	45
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	BT28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	3.5
Diameter (mm)	89
Family Brand Name	Compact Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	135.00

Nominal Wattage (W)	400.00
Operating Position	Universal
Warm-up Time (min)	2-4

**Additional Product Information****Product Documents, Graphs, and Images****Compatible Ballast****Packaging Information****Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.

[Print Page](#)