

[Return to search](#)[Print Page](#)

Product Number: 64578

Order Abbreviation: MS250/PS/BU-ONLY

General Description: 250W METALARC PULSE START quartz metal halide lamp, high output, position dedicated, reduced color shift, E39 base, BT37 bulb, enclosed fixture rated, base up only, clear, 4200K

Product Information

| | |
|---------------------------------------|---------------------------|
| Abbrev. With Packaging Info. | MS250PSBUONLY 6/CS 1/SKU |
| ANSI Code | M153/E: M138/E |
| Approx. Lumens (initial - vertical) | 23000 |
| Approx. Lumens (mean - vertical) | 17000 |
| Arc Length (in) | 1.38 |
| Arc Length (mm) | 35 |
| Average Rated Life - Vertical (hr) | 20000 |
| Base | E39 Mogul |
| Bulb | BT28 |
| Color Rendering Index (CRI) | 65 |
| Color Temperature/CCT (K) | 4200 |
| Diameter (in) | 3.5 |
| Diameter (mm) | 89 |
| Family Brand Name | Metalarc® Pulse Start |
| Fixture Requirement | E |
| Hot Restrike Time (min) | 5-7 |
| Lamp Finish | Clear |
| Light Center Length - LCL (in) | 5 |
| Light Center Length - LCL (mm) | 127 |
| Maximum Base Temperature - Fahrenheit | 482 |
| Maximum Base Temperature - Celsius | 250 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 8.31 |
| Maximum Overall Length - MOL (mm) | 211 |
| Nominal Voltage (V) | 133.00 |
| Nominal Wattage (W) | 250.00 |
| Operating Position | Base up within 15deg only |
| Warm-up Time (min) | 2-4 |

Additional Product Information**Product Documents, Graphs, and Images****Packaging Information****Footnotes**

- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- When operated on ballasts having a sustaining voltage less than 270V, lamp life may be significantly reduced.*

[Print Page](#)