

[Return to search](#)[Print Page](#)

Product Number: 64815

Order Abbreviation: MS175/PS/BU-ONLY

General Description: 175W METALARC PULSE START quartz metal halide lamp, reduced color shift, E39 base, ED28 bulb, enclosed fixture rated, base up only, clear, 4000K

Product Information

Abbrev. With Packaging Info.	MS175PSBUONLY 12/CS 1/SKU
ANSI Code	M152/E: M137/E
Approx. Lumens (initial - horizontal) 2	17500
Approx. Lumens (initial - vertical)	17500
Approx. Lumens (mean - vertical)	12800
Arc Length (in)	0.811
Arc Length (mm)	20.6
Average Rated Life - Vertical (hr)	15000
Base	E39 Mogul
Bulb	ED28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	3.5
Diameter (mm)	89
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	2-4
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Wattage (W)	175.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Additional Product Information**Product Documents, Graphs, and Images****Packaging Information****Footnotes**

- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- When operated on ballasts having a sustaining voltage less than 270V, lamp life may be significantly reduced.*
- Lamps may be operated on ANSI M137 Compliant ballasts.

| Print Page |