



Product Number: 64878

Order Abbreviation: MCP20PAR30LN/U/830/FL/ECO PB

General Description: 20W high CRI, powerball arc tube, reduced color shift, high performance, ECO open fixture rated Par30 Lamp, clear, flood, universal

Product Information

Product Information	
Abbrev. With Packaging Info.	MCP20PAR30LNU830FLECO PB 6/CS 1/SKU
ANSI Code	M156/O
Approx. Lumens (initial - horizontal)	1200
Approx. Lumens (initial - vertical)	1200
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Average Rated Life - Vertical (hr)	12000
Avg Rated Life (hrs)	12000
Base	E26 Medium
Beam Angle (deg)	30
Beam Type	FL
Bulb	PAR30LN
Centerbeam Candlepower (cp)	4000
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	3100
Diameter (in)	3.752
Diameter (mm)	95.30
Family Brand Name	Metalarc® Powerball
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Clear
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	572
Maximum Bulb Temperature - Celsius	300
Maximum Overall Length - MOL (in)	4.76
Maximum Overall Length - MOL (mm)	121
Nominal Wattage (W)	20.00

Operating Position	Universal
Warm-up Time (min)	2-4



ECOLOGIC

™

**Footnotes**

- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- UV-Stop quartz