



Product Number: 64880

Order Abbreviation: MCP39PAR30LN/U/830/SP/ECO PB

General Description: 39 watt Powerball ceramic arc tube, high CRI, ecologic, color consistent, medium base, open fixture rated, PAR30, clear metal halide lamp

Product Information	
Abbrev. With Packaging Info.	MCP39PAR30LNU830SPECOPB 6/CS 1/SKU
ANSI Code	C130/O
Approx. Lumens (initial - horizontal)	2300
Approx. Lumens (initial - vertical)	2300
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Avg Rated Life (hrs)	12000
Base	E26 Medium
Beam Angle (deg)	10
Beam Type	SP
Bulb	PAR30LN
Centerbeam Candlepower (cp)	39600
Color Rendering Index (CRI)	85
Color Temperature/CCT (K)	3000
Diameter (in)	3.752
Diameter (mm)	95.30
Family Brand Name	Metalarc® Powerball
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Clear
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	572
Maximum Bulb Temperature - Celsius	300
Maximum Overall Length - MOL (in)	4.76
Maximum Overall Length - MOL (mm)	121
Nominal Wattage (W)	39.00
Operating Position	Universal

Warm-up Time (min)	2-4
--------------------	-----



ECOLOGIC

TM

**Footnotes**

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz