

STYLE NO:21079

Parts and Hardware List

A	Ceiling Assembly	1pc
B	Ball Nut	2pcs
C	Glass	3pcs
D	Universal bar	1pc
E	Mounting Screws	2pcs
F	Green Screw	1pc
G	Wire Nut	2pcs
H	Outlet box screw	2pcs

Please make sure that you have all the parts indicated before you begin assembly of this item

Please read Wiring Instructions before you begin assembling and installing your Ceiling Lamp.

WARNING: BEFORE INSTALLING Make sure electricity supply is shut off to avoid a possible electric shock

Assembly Instructions

1. Carefully remove the parts and hardware from the carton.
2. Remove Ball Nuts under the Ceiling Pan from Mounting Screws, and take out the Universal bar . Attach the Universal bar to the ceiling outlet box by using two outlet box screws.(See Figure1)
3. Install the ground wire in the universal bar with the green screws supplied.
4. Place the white ,ribbed or tinted wire evenly against the white wire from the outlet box and place the black, smooth or un-tinted wire evenly against the black wire from the outlet box. (Connecting the Wires-See Figure2)
5. After the wires are connected,tuck them carefully inside the outlet box. Attach the Ceiling Assembly to Mounting Screws and secure with two Ball nuts(See Figure1)
6. Attach the Glass onto the socket of Ceiling Assembly using the socket ring.
7. Install 100 Watt, Type A bulbs(sold separately) into the sockets of the fixture.

CLEANING: This item has a lacquered and baked finish. When cleaning only use a soft, dry cloth. Do not use liquid cleansers or abrasives as they may damage the finish.

