

Parts and Hardware List

A.	Glass sticks	102PCS
B.	Square bead	39PCS
C.	Square bead and crystal ball (long)	39PCS
D.	Square bead and crystal ball (short)	39PCS
E.	Crystal finial	1PC
F.	Pre-Threaded Pipe	1PC
G.	Hex Nut	1PC
H.	Pre-Threaded Ring	1PC
I.	Collar loop	1PC
J.	Canopy	1PC
K.	Wire Nut	2PCS
L.	Chain	1PC
M.	Quick Link	2PCS
N.	LOOP	1PC
O.	Cross Bar	1PC
P.	Pipe nipple	1PC
Q.	Shutter	1PC
R.	Outlet box screws	2PCS

Please make sure that you have all the parts indicated before you begin assembly of this item.

Please read wiring Instructions before you begin assembling and installing your Chandelier.

WARNING: BEFORE INSTALLING Make sure electricity supply is shut off to avoid a possible electric shock.

Assembly Instructions

- Carefully remove the parts and hardware from the carton.
- Fasten the Cross Bar (O) to the outlet box using the Outlet box Screws.
- Insert the shorter end of the Pre-Threaded Pipe (F) into the pre-drilled hole in the Cross Bar(O) and secure with the Hex Nut(G).See Illustration.
- Attach the Collar Loop (I) to the exposed end of the Pre-Threaded Pipe (F)and secure by turning in a clockwise direction.
- Attach the Quick Link on other end of the Chain(L) to Collar Loop (I).
- Slip the Pre-Threaded Ring(H) first and then the Canopy (J) over the other end of the Chain (L)
- Attach the other Quick Link on other end of the Chain (L)to the loop on the top of Chandelier Assembly (A).
- Lace the wire through the chain ,through the collar loop and up through the Pre-Threaded Pipe(F) See Illustration.
- Place the white ,ribbed or tinted wire evenly against the white wire from the outlet box and place the black,smooth or un-tinted wire evenly against the black wire from the outlet box (Connecting the Wires-See Figure2)
- Install the ground wire in the Cross Bar with the green screw supplied.
- After the wires are connected,tuck them carefully inside the outlet box ,Place Canopy (J) over the outlet box and secure with Pre-Threaded Ring(H).
- Hanging the glass sticks and crystal beads from inside to outside in turn of A to D, Crystal B and C are hang in the same metal ring one by one.
- Screw the pipe nipple clockwise to coupling nut until secure.
- Attach the shutter in the pipe nipple the secure by Crystal finial turning a clockwise direction.
- Install 60 Watt, Type B bulbs (sold separately) into the sockets of the fixture.

Notice:

Please hang the crystal ball to the end of crystal strand when it dropped out of the strand.

If the fixture hanging crystal can't be on a level,please note the three weights on the frame in the tube are moveable ,they are used to balance and make the fixture hang level.

