

Lighting

Commercial Products & Solutions

→ HOME **PRODUCTS** ▶ EDUCATION / RESOURCES LIGHTING APPLICATIONS SITE SEARCH


Where to Buy | FAQs | Contact Us | EliteNet

PRINT

Products > 10310

10310 - F30T8/D

GE Daylight Starcoat® T8






GENERAL CHARACTERISTICS

Lamp type	Linear Fluorescent - Straight Linear
Bulb	T8
Base	Medium Bi-Pin (G13)
Wattage	30
Voltage	99
Rated Life	7500 hrs
Bulb Material	Soda lime
Starting Temperature (MIN)	10 ℃ (50 ℉)
Picograms of Mercury	656 picograms



PHOTOMETRIC CHARACTERISTICS

Initial Lumens	1850			
Mean Lumens	1625			
Nominal Initial Lumens per Watt	61			
Color Temperature	6500 K			
Color Rendering Index (CRI)	75			



View Larger


ELECTRICAL CHARACTERISTICS

LLLOTRIOAL OTTAKAOTERIOTIOO							
Open Circuit Voltage (after preheating) Max @ Temperature	375 V @ 10 ℃						
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25						
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5						
Open Circuit Voltage (after preheating) Min @ Temperature	176 V @ 10 ℃						
Current Crest Factor (MAX)	1.7						



GRAPHS & CHARTS

Spectral Power Distribution



Lamp Mortality

DIMENSIONS

35.7800 in (908.8 mm)
35.6700 in (906.0 mm)
36.000 in (914.4 mm)
1.000 in (25.4 mm)
0.940 in (23.8 mm)
1.100 in (27.9 mm)
35.220 in (894.5 mm)

Face to End of Opposing Pin (B) (MIN)	35.400 in (899.1 mm)
Face to End of Opposing Pin (B) (MAX)	35.500 in (901.7 mm)
End of Base Pin to End of Opposite Pin End (C)	35.670 in (906.0 mm)

90% -	\vdash	-	_		_	-		-
90% - 80% - 70% -						-	$\overline{}$	
70% -							1	
60% -				_		- 0		1
50% -		187	7.5	375	. 0	56	26	750
	J	18	O	3/5	U	26	20	10

P	R	0	DI	JCT	INI	FOI	РM	ΔΤ	ION
г	Γ	v	ν	J G I	1131			\sim 1	IUI

Product Code	10310
Description	F30T8/D
ANSI Code	2018-1
Standard Package	Case
Standard Package GTIN	10043168103104
Standard Package Quantity	24
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168103107



See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2008