

Lighting

Commercial Products & Solutions

→ HOME **PRODUCTS** ▶ EDUCATION / RESOURCES LIGHTING APPLICATIONS SITE SEARCH

Where to Buy | FAQs | Contact Us | EliteNet

₽RINT

Products > Halogen > MR > MR16 > 20858

20858 - Q20MR16C/CG15ESX

GE ConstantColor® Precise™ MR16


• UV protection

Lamp type

Filament Wattage

Voltage

Bulb Base



Rated Life	5000 hrs
Lamp Enclosure Type (LET)	Covered glass

12

PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower (CBCP)	3150
Color Temperature	2900 K
Nominal Initial Lumens per Watt	157

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
DIMENSIONS	
Maximum Overall Length (MOL)	1.8750 in (47.6 mm)
Bulb Diameter (DIA)	2.000 in (50.8 mm)

DDODUCT INFORMATION

PRODUCT INFORMATION	
Product Code	20858
Description	Q20MR16C/CG15ESX
ANSI Code	ESX
Standard Package	BUNDLE
Standard Package GTIN	00043168208581
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168992961

A CAUTIONS & WARNINGS

See list of cautions & warnings.









View Larger

ADDITIONAL RESOURCES

Catalogs

Testimonials

Brochures

Product Brochures

- Color
- XL Brochure

Application/Segment Brochures

- Contractor Lighting
- Healthcare Lighting
- Office Lighting
- Specialty Store Lighting

Sell Sheets

GE ConstantColor® Precise™ MR16 Lamps

IES/Photometric Download

MSDS (Material Safety Data Sheets)

Disposal Policies & Recycling Information

20858 - Specifications - GE Commercial Lighting Products	Page 2 of 2
	Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2008