

GE Lighting

### WORLDWIDE PARTNER

Commercial Products & Solutions

SITE SEARCH > HOME \* PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS

Where to Buy | FAQs | Contact Us | EliteNet

₽RINT

Products > Halogen > MR > MR16 > 20867

# 20867 - Q50MR16C/CG40

GE ConstantColor® Precise™ MR16

UV protection

GENERAL CHARACTERISTICS		
Lamp type	Halogen - MR	
Bulb	MR16	
Base	2-Pin (GU5.3)	
Filament	C-6	
Wattage	50	
Voltage	12	
Rated Life	6000 hrs	
Lamp Enclosure Type (LET)	Covered glass	

### PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower (CBCP)	1500
Color Temperature	3050 K
Nominal Initial Lumens per Watt	30

# **ELECTRICAL CHARACTERISTICS**

Burn Position	Universal burning position
DIMENSIONS	
Maximum Overall Length (MOL)	1.8750 in (47.6 mm)
Bulb Diameter (DIA)	2.000 in (50.8 mm)

### PRODUCT INFORMATION

PRODUCT INFORMATION		
Product Code	20867	
Description	Q50MR16C/CG40	
ANSI Code	EXN	
Standard Package	BUNDLE	
Standard Package GTIN	00043168208673	
Standard Package Quantity	20	
Sales Unit	Unit	
No Of Items Per Sales Unit	1	
No Of Items Per Standard Package	20	
UPC	043168994194	

**A** CAUTIONS & WARNINGS

See list of cautions & warnings.









View Larger

# ADDITIONAL RESOURCES

# **Catalogs**

## **Testimonials**

#### **Brochures**

**Product Brochures** 

- Color
- XL Brochure

Application/Segment Brochures

- Contractor Lighting
- Healthcare Lighting
- Office Lighting
- Restaurant Lighting
- Specialty Store Lighting

## **Sell Sheets**

GE ConstantColor® Precise™ MR16 Lamps

**IES/Photometric Download** 

MSDS (Material Safety Data Sheets)

**Disposal Policies & Recycling Information** 

20867 - Specifications - GE Commercial Lighting Products	Page 2 of 2
	Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2008