



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > [Halogen](#) > [MR](#) > [MR16](#) > 41488
41488 – Q50MR16/CCG15


GE ConstantColor® Precise™ MR16



- UV protection

GENERAL CHARACTERISTICS

Lamp type	Halogen - MR
Bulb	MR16
Base	2-Pin (GU5.3)
Filament	C-6
Wattage	50
Voltage	24
Rated Life	4000 hrs
Lamp Enclosure Type (LET)	Covered glass

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Center Beam Candlepower (CBCP)	8400
Color Temperature	2950 K
Nominal Initial Lumens per Watt	168

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
---------------	----------------------------

DIMENSIONS

Maximum Overall Length (MOL)	1.8750 in (47.6 mm)
Bulb Diameter (DIA)	2.000 in (50.8 mm)

PRODUCT INFORMATION

Product Code	41488
Description	Q50MR16/CCG15
Standard Package	BUNDLE
Standard Package GTIN	30043168414884
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168414883

CAUTIONS & WARNINGS
[See list of cautions & warnings.](#)
ADDITIONAL RESOURCES**Catalogs****Testimonials****Brochures**

Application/Segment Brochures

- [Contractor Lighting](#)
- [Healthcare Lighting](#)
- [Office Lighting](#)

Sell Sheets

- [GE 24 Volt Halogen Lighting System](#)

MSDS (Material Safety Data Sheets)**Disposal Policies & Recycling Information**

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2008