



Commercial Products &amp; Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 45680**45680 – CMH100PAR38SPECO**


GE ConstantColor® PulseArc® CMH® Ceramic Metal Halide PAR38



- Passes TCLP, which can lower disposal costs.

 a product of  
**ecomagination**™
**GENERAL CHARACTERISTICS**

Lamp type	High Intensity Discharge - Ceramic Metal Halide
Bulb	PAR38
Base	Medium Screw (E26)
Wattage	100
Rated Life	10000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
LEED-EB MR Credit	112 picograms Hg per mean lumen hour
Additional Info	TCLP compliant, UV control

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	6500
Nominal Initial Lumens per Watt	65
Beam Spread	15 °
Center Beam Candlepower (CBCP)	45000
Color Temperature	3000 K
Color Rendering Index (CRI)	81

**ELECTRICAL CHARACTERISTICS**

Burn Position	Universal burning position
Open Circuit Voltage (peak lead ballast) (MIN)	332 V/332 V
Open Circuit Voltage (RMS lag ballast) (MIN)	235 V
Warm Up Time to 90% (MAX)	2 min/3 min
Hot Restart Time to 90% (MIN)	10 min
Hot Restart Time to 90% (MAX)	15 min

**DIMENSIONS**

Maximum Overall	5.3100
-----------------	--------

**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)[Sell Sheets](#)

- [GE ConstantColor® CMH® Lamps](#)

[IES/Photometric Download](#)[MSDS \(Material Safety Data Sheets\)](#)[Disposal Policies & Recycling Information](#)

Length (MOL)	
Nominal Length	5.310
Bulb Diameter (DIA)	4 3/4

**PRODUCT INFORMATION**

Product Code	45680
Description	CMH100PAR38SPECO
ANSI Code	M140/M90
Standard Package	Case
Standard Package GTIN	10043168456804
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168456807

**COMPATIBLE GE BALLASTS**

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
<a href="#">86574</a>	11210239CTC000I	1	90.0	1.0
<a href="#">86667</a>	GEM10048TLC3D-5	1	90.0	1.0
<a href="#">86675</a>	GEM100MLTLC3D-5	1	90.0	1.0
<a href="#">87561</a>	GEMH100-SLJ-MV	1	98.0	1.0

**⚠ CAUTIONS & WARNINGS**

**R-** WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information:  
<http://www.fda.gov/cdrh/radhealth/products/urburns.html>

[See list of cautions & warnings.](#)

**NOTES**

- Rated life based on 11 hours per start

[Return To Top](#)