1		
	GE Lighting	
	Lighting	
WORLDWIDE PAR	RTNER	Commercial Products & Solutions
<u></u>	HOME	* PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS
		Where to Buy FAQs Contact Us EliteNe
Products > Compac	t Fluorescent > Indoor Floodlight > 80	0893
80893 - FLE15/ GE Floodlight Soft V	/2/R30XL827 Vhite R30 - Facilities; Retail Display; I	Hospitality; Office; Restaurant
a product of ecomagination		
Migh C	olor Rendering	
CUL Lis	-	
	r Savings	
(UL List	ea	-
GENERAL CHARA		
Lamp type	Compact Fluorescent - Self- Ballasted	Bulb Base
Bulb	R30	
Base	Medium Screw (E26)	
ENERGY STAR® Qualified	Yes	
Wattage	15	View Larger
Equivalent Wattage	65 W	
Rated Life	10000 hrs	ADDITIONAL RESOURCES
Starting Temperature (MIN)	-15 °C (5 °F)	<u>Catalogs</u> Testimonials
Picograms of Mercury	467 picograms	Brochures Product Brochures
Primary Application	Indoor Floodlight; Facilities; Retail Display; Hospitality; Office; Restaurant	<u>GE Consumer & Industrial ENERGY STAR®</u> <u>Program</u> IES/Photometric Download
		Disposal Policies & Recycling Information
PHOTOMETRIC CH		
Initial Lumens	750	
Nominal Initial Lumens per Watt	50	
Color Temperature	2700 K	
Color Rendering Index (CRI)	82	
ELECTRICAL CHA	RACTERISTICS	-
Input Voltage	120 V	
Input Current	0.2300 A	<u> </u>
DIMENSIONS		
DIMENSIONS Maximum Overall	5.5000 in (139.7 mm)	_
Length (MOL) Nominal Length	5.500 in (139.7 mm)	_
	0.000 III (100.7 IIIII)	
	IATION	
Product Code	80893	
Description	FLE15/2/R30XL827	_

Standard Package	Case
Standard Package GTIN	10043168808931
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168808934

A CAUTIONS & WARNINGS

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2008