

**PRISM®**  
 < SureColor™ MR16



## PRISM® SureColor™ MR16



### Technical Data

- GU5.3 base
- White light 2950-3100K
- Cool beam dichroic reflector
- Titanium-coated reflector prevents deterioration, ensuring consistent color throughout lamp life
- UV-stop quartz capsule
- C-8 Axial filament
- High lumen maintenance – over 90% throughout lamp life

### Long Life

- 5,000 Hours Average Rated Life

### Benefits

- No color shift
- No light loss caused by degradation of dichroic coating
- Greatly reduces fading caused by UV exposure
- Precise beam control

### Applications

- Retail lighting
- Display/Accent lighting
- General lighting

The **SureColor™** mark guarantees consistent color, precise beam control and long life.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at [halcolighting.com](http://halcolighting.com).

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.

**ISO 9001 Certified**



where there's light,  
 there's halco®

(800) 677-3334  
[halcolighting.com](http://halcolighting.com)

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/ Qty	Volts	CBCP	Color Temp	Avg Rated Life	Filament Design	MOL (Inches)	Beam Spread
MR16	20	GU5.3	107120	MR16BAB/SC	Flood	10/100	12	700	2950	5000	C-8	1.77"	38°
MR16	20	GU5.3	107121	MR16BAB/L/SC	Flood w/Lens	10/100	12	700	2950	5000	C-8	1.77"	38°
MR16	20	GU5.3	107350	MR16BAB/BLK/L	Flood Black Aluminized Reflector w/Lens	10/100	12	900	2950	5000	C-8	1.77"	38°
MR16	20	GU5.3	107440	MR16BBF/L/SC	Medium Flood w/Lens	10/100	12	1500	2950	5000	C-8	1.77"	20°
MR16	20	GU5.3	107122	MR16ESX/SC	Narrow Spot	10/100	12	4000	2950	5000	C-8	1.77"	10°
MR16	20	GU5.3	107123	MR16ESX/L/SC	Narrow Spot w/Lens	10/100	12	4000	2950	5000	C-8	1.77"	10°
MR16	20	GU5.3	107090	MR16WFL20/SC	Wide Flood	10/100	12	450	2950	5000	C-8	1.77"	60°
MR16	20	GU5.3	107400	MR16WFL20/L/SC	Wide Flood w/Lens	10/100	12	450	2950	5000	C-8	1.77"	60°
MR16	20	GU5.3	107300	MR16BAB/FR/SC	Flood Frost w/Lens	10/100	12	450	2950	5000	C-8	1.77"	38°
MR16	35	GU5.3	107141	MR16FRA/L/SC	Spot w/Lens	10/100	12	3000	3000	5000	C-8	1.77"	20°
MR16	35	GU5.3	107136	MR16FRB/SC	Spot	10/100	12	8000	3000	5000	C-8	1.77"	10°
MR16	35	GU5.3	107420	MR16FRB/L/SC	Spot w/Lens	10/100	12	8000	3000	5000	C-8	1.77"	10°
MR16	35	GU5.3	107138	MR16FMW/SC	Flood	10/100	12	1500	3000	5000	C-8	1.77"	38°
MR16	35	GU5.3	107139	MR16FMW/L/SC	Flood w/Lens	10/100	12	1500	3000	5000	C-8	1.77"	38°
MR16	35	GU5.3	107362	MR16FMW/BLK/L	Flood Black Aluminized Reflector w/Lens	10/100	12	1700	3000	5000	C-6	1.77"	36°
MR16	35	GU5.3	107092	MR16WFL35/SC	Wide Flood	10/100	12	800	3000	5000	C-8	1.77"	60°
MR16	35	GU5.3	107430	MR16WFL35/L/SC	Wide Flood w/Lens	10/100	12	800	3000	5000	C-8	1.77"	60°
MR16	50	GU5.3	107124	MR16EXN/SC	Flood	10/100	12	2000	3050	5000	C-8	1.77"	38°
MR16	50	GU5.3	107125	MR16EXN/L/SC	Flood w/Lens	10/100	12	2000	3050	5000	C-8	1.77"	38°
MR16	50	GU5.3	107356	MR16EXN/BLK/L	Flood Black Back Aluminized Reflector w/Lens	10/100	12	2200	3050	5000	C-8	1.77"	36°
MR16	50	GU5.3	107358	MR16EXN/SIL/L	Flood Silver Back Aluminized Reflector w/Lens	10/100	12	2200	3050	5000	C-8	1.77"	36°
MR16	50	GU5.3	107126	MR16EXT/SC	Spot	10/100	12	10000	3050	5000	C-8	1.77"	10°
MR16	50	GU5.3	107127	MR16EXT/L/SC	Spot w/Lens	10/100	12	10000	3050	5000	C-8	1.77"	10°
MR16	50	GU5.3	107128	MR16EXZ/SC	Narrow Flood	10/100	12	4000	3050	5000	C-8	1.77"	20°
MR16	50	GU5.3	107129	MR16EXZ/L/SC	Narrow Flood w/Lens	10/100	12	4000	3050	5000	C-8	1.77"	20°
MR16	50	GU5.3	107146	MR16FNV/SC	Wide Flood	10/100	12	1050	3050	5000	C-8	1.77"	60°
MR16	50	GU5.3	107410	MR16FNV/L/SC	Wide Flood w/Lens	10/100	12	1050	3050	5000	C-8	1.77"	60°
MR16	50	GU5.3	107304	MR16EXN/FR/SC	Flood Frost w/Lens	10/100	12	1050	3050	5000	C-8	1.77"	38°
MR16	75	GU5.3	107130	MR16EYC/SC	Flood	10/100	12	2750	3100	5000	C-8	1.77"	38°
MR16	75	GU5.3	107132	MR16EYF/SC	Spot	10/100	12	13000	3100	5000	C-8	1.77"	10°
MR16	75	GU5.3	107134	MR16EYJ/SC	Narrow Flood	10/100	12	6000	3100	5000	C-8	1.77"	20°
MR16	75	GU5.3	107312	MR16WFL75/SC	Wide Flood	10/100	12	1400	3100	5000	C-8	1.77"	60°
MR16	75	GU5.3	107314	MR16WFL75/L/SC	Wide Flood w/Lens	10/100	12	1400	3100	5000	C-8	1.77"	60°

Made in Spain