

## Malibu<sup>®</sup> Low Voltage Landscape Lighting



## Low Voltage Polymer







LV108/ML90708



LV183/ML11183





LX1/ML10401

## **Power Packs**

Intermatic offers the widest variety of Power Packs in any wattage and control option your system may require. Power Packs are available from 44 to 900 watts, allowing you to choose which power supply is right for your particular lighting plan.

All Power Packs are certified for safe operation and long life. Keyhole mountings are featured for ease of operation and installation. See chart below for available Power Packs and features.

Models	Max. Wattage Output	Specifications
ML44T	44 Watt	Timer with 2 sets of trippers
ML88T	88 Watt	Timer with 2 sets of trippers
ML100T	100 Watt	Timer with 2 sets of trippers
ML100THB	100 Watt	Electronic Timer and photo control
ML121RT	121 Watt	Timer with 2 sets of trippers
ML200RT	200 Watt	Timer with 2 sets of trippers
ML200RTW	200 Watt	Timer with 2 sets of trippers and ground shield
ML300RTW	300 Watt	Timer with 2 sets of trippers and ground shield
ML600TW	600 Watt	Timer with 2 sets of trippers and ground shield
ML900TW	900 Watt	Timer with 2 sets of trippers and ground shield

IMPORTANT: When planning your lighting and choosing a Power Pack, your total bulb wattage must not exceed maximum transformer wattage output rating.

## **Power Pack Models**



ML44T **ML88T** 



ML100THB



**ML100T** ML200RTW



ML300RTW

**ML121RT** ML200RT



Low Voltage Cable For fast, easy installation of Malibu® light fixtures, use low voltage cable. It's safe, weather-resistant, self sealing and available in 16, 14 and 12 gauge sizes.



ML600TW

ML900TW

