

MSR Gold™ SA Double Ended

MSR Gold™ 1510 SA/DE 1CT

To optimize the total lifetime of the double ended MSR Gold[™] SA Double Ended lamps, the caps are plated with gold. This provides superior heat protection and thereby minimizes premature failure of the lamp and lamp holder, as well as ensuring extended consistent performance. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which further extends service life and consistency of high-quality light output.

Product data

• General Characteristics

System Description	SA/DE
Cap-Base	SFC10-4
Cap-Base Information	SFC10-4
Execution	-
Operating Position	any
Main Application	Entertainment
Life to 50% failures	750 hr
EM	

• Light Technical Characteristics

Color Code Color Rendering Index	- 85 Ra8				
Color Temperature	6000 K				
Color Temperature	6000 K				
Technical	224				
Chromaticity Coor- dinate X	326 -				
Chromaticity Coor-	336 -				
dinate Y	550 -				
Luminous Flux Lamp	140000 Lm				
EM					
Luminous Efficacy	93 Lm/W				
Lamp EM					

• Electrical Characteristics

Watts	1500 W
Lamp Wattage Tech-	1500 W
nical	

Lamp Current	
Ignition Supply	
Voltage	
Dimmable	

Yes

13.5 A 198 (min) V

Luminaire Design Requirements

Pinch Temperature	500 (max) C
Bulb Temperature	950 (max) C

Product Dimensions

Base Face to Base Face A Overall Length C Diameter D Arc Length O 114.4 (min), 114.8 (nom), 115.2 (max) mm 136 (max) mm 23 (max) mm 7.0 mm

• Product Data

Product number Full product name Short product name Pieces per Sku eop_pck_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop_net_weight_pp


245258 MSR Gold™ 1510 SA/DE 1CT MSR Gold 1510 SA/DE 1CT/16

1 16 16 8727900912760 8727900912777 928176605114 0.034 kg





Dimensional drawing




MSR Gold™ SA/DE

Product	A (Min)	A (Norm)	A (Max)	C (Max)	D (Max)	D1 (Norm)	F (Min)	F (Norm)	F (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
MSR GOLD 1510 SA/DE	114.4	114.8	115.2	136	23	-	-	-	-	-	-	-	7.0




SFC10-4

Photometric data



MSR Gold™ 1200 SA/DE, MSR Gold™ 1510 SA/DE



MSR Gold™ 1200 SA/DE, MSR Gold™ 1510 SA/DE



 $\ensuremath{\textcircled{}^{\circ}}$ 2012 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting