

Halogen Low Voltage

ELC/5H 250W 24V

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of highquality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

Product data

• General Characteristics

Philips Code 13163 ELC/5H ANSI Code LIF Code GX5.3 Cap-Base Bulb R50

Bulb Material Quartz-UV Open Reflector Finish Smooth

Operating Position s90 Projection Main Application Life to 50% failures 500 hr

• Light Technical Characteristics

Color Rendering 100 Ra8

Index

3400 K Color Temperature

Technical

• Electrical Characteristics

Watts 250 W Voltage 24 V Dimmable Yes

• Luminaire Design Requirements

Pinch Temperature 400 (max) C

Dimensional drawing

Bulb Temperature Working Distance WD

900 (max) C 32 mm

• Product Dimensions

Overall Length C 44.5 (max) mm Diameter D 50 (max) mm Filament Dimensions (WxH) [mm]

• Product Data

Product number 381665 Full product name

13163 ELC/5H 250W GX5.3 24V

Short product name 13163 ELC/5H 250W GX5.3 24V


1CT/24

Pieces per Sku 24 eop pck cfg Skus/Case 24

8711500413475 Bar code on pack 8711500435736 Bar code on case Logistics code(s) 924862720540 24.000 gr eop_net_weight_pp



Dimensional drawing



GX5.3, GY5.3, GZ6.35

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)
ELC/5H 250W GX5.3 24V	44.5	50	-	-	-



GX5.3



 $\ensuremath{@}$ 2012 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.