



20W Med EL/A R40 Dim ALTO 1CT

Product family description

Similar look and light output as a 65 Watt incandescent BR30 reflector flood. Diffused, Soft White Light - Wide flood provides smooth, even lighting without hot spots.

Suitable for use in wet locations.

Amalgam Technology - Provides stable light over a broad range of temperatures. Super Long Life - Lasts 5 years, based on 3- 4 hours average daily usage, 7 days per week (up to 7 times longer than standard incandescent lamps).

Energy Savings - Saves up to 75% in electricity costs compared to incandescent lamps.

ENERGY STAR Qualified.

Applications

- Ideal for recessed and track lighting fixtures, indoors and outdoors.

Notes

- The use of Amalgam Technology results in relatively stable light output across a broad range of ambient temperatures and operating positions. (216)
- All Marathon™ lamps are suitable for indoor or outdoor use down to - 10°F. Outdoor use requires a weather-protected fixture. All these products comply with part 18 of the FCC rules. These products may cause interference with AM radios, cordless telephones, and remote control devices. Interference may be caused after a brief 90-second lamp warm-up period. If interference continues, relocate the lamp away from the device or plug into a different outlet. (217)
- All lamps are electronically ballasted and designed for 120 volt operation. Lamps operated in extreme environments will have reduced life (ie. recessed or enclosed lighting fixtures with elevated line voltage). Caution: except for lamps marked dimmable, do not use with dimmers. Before using these lamps with electronic timing or photocell devices, check to determine whether the device is compatible with compact fluorescent lamps. Use with incompatible devices will result in premature lamp failure. These products are UL listed. (218)
- Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. (230)
- Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions. (231)

| Product data | |
|-------------------|-------------------------------|
| Product Number | 137083 |
| Full product name | 20W Med EL/A R40 Dim ALTO 1CT |
| Ordering Code | EL/A R40 20W DIMM REFLECTOR |
| Pack type | 1 Lamp in a Folding Carton |
| Pieces per Sku | 1 |
| Skus/Case | 6 |
| Pack UPC | 046677137083 |
| EAN2US | |
| Case Bar Code | 50046677137088 |

PHILIPS

| Product data | |
|------------------------------|--------------------------------------|
| Successor Product number | |
| Base | Medium [Single Contact Medium Screw] |
| Bulb | EL/A R40 |
| Packing Type | 1CT [1 Lamp in a Folding Carton] |
| Packing Configuration | 6 |
| Feature | Dimmable ALTO® |
| Rated Avg. Life [3 hr Start] | 8000 hr |
| Ordering Code | EL/A R40 20W DIMM REFLECTOR |
| Pack UPC | 046677137083 |
| Case Bar Code | 50046677137088 |
| Energy Saving | Energy Saving |
| Watts | 20W |
| Color Rendering Index | 82 Ra8 |
| Color Temperature | 2700 K |
| Initial Lumens | 900 Lm |
| Max Overall Length (MOL) - C | 6.06 in |
| Product Number | 137083 |



CI RefID Medium EL/A R40



Base Medium



Energy Saving Energy Saving

