

Halogen

PAR-36, PAR-38 Lamps

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.*	Description	Class, Filament	MOL (in.)	Rated Avg. Life (93)	Approx MBCP*	Lumens
Halogen PAR-36 Lamps													
50	PAR-36	MP	13082-3	\$	50PAR36Q/VNSP6	12	12	PAR, Narrow Spot	C, C-6	2 3/4	4000	35,000	400
Halogen PAR-38 Lamps (82, 86)													
45	PAR-38	Med.Skt.	22946-8	\$	45PAR38/HAL/SP10	120	12	Spot 10°	C, CC-8	5 3/8	3000	6200	530
	Standard Reflector		22948-4	\$	45PAR38/HAL/FL25	120	12	Flood 25°	C, CC-8	5 3/8	3000	2000	530
60	PAR-38	Med.Skt.	14482-4	\$	60PAR38/HAL/SP10	120	12	Spot 10°	C, CC-8	5 3/8	3000	10,500	800
	Standard Reflector		14483-2	\$	60PAR38/HAL/FL25	120	12	Flood 25°	C, CC-8	5 3/8	3000	3200	800
			14484-0	\$	60PAR38/HAL/WFL40	120	12	W. Flood 40°	C, CC-8	5 3/8	3000	1300	800
75	PAR-38	Med.Skt.	14485-7	\$	75PAR38/HAL/SP10	120	12	Spot 10°	C, CC-8	5 3/8	3000	13,000	1050
	Standard Reflector		14486-5	\$	75PAR38/HAL/FL25	120	12	Flood 25°	C, CC-8	5 3/8	3000	3800	1050
90	PAR-38	Med.Skt.	23069-8	\$	90PAR38/HAL/SP10	120	12	Spot 10°	C, CC-8	5 3/8	3000	16,400	1350
	Standard Reflector		23070-6	\$	90PAR38/HAL/FL25	120	12	Flood 25°	C, CC-8	5 3/8	3000	5350	1350
			14487-3	\$	90PAR38/HAL/WFL40	120	12	W. Flood 40°	C, CC-8	5 3/8	3000	2200	1350
Halogen PAR-38 Lamps 130V (82, 86)													
45	PAR-38	Med.Skt.	22947-6	\$	45PAR38/HAL/SP10	130	12	Spot 10°	C, CC-8	5 3/8	2500	6200	530
	Standard Reflector		22949-2	\$	45PAR38/HAL/FL25	130	12	Flood 25°	C, CC-8	5 3/8	2500	2000	530
60	PAR-38	Med.Skt.	14488-1	\$	60PAR38/HAL/SP10	130	12	Spot 10°	C, CC-8	5 3/8	3000	10,500	800
	Standard Reflector		14490-7	\$	60PAR38/HAL/FL25	130	12	Flood 25°	C, CC-8	5 3/8	3000	3200	800
			14491-5	\$	60PAR38/HAL/WFL40	130	12	W. Flood 40°	C, CC-8	5 3/8	3000	1300	800
75	PAR-38	Med.Skt.	14492-3	\$	75PAR38/HAL/NSP8	130	12	N. Spot 8°	C, CC-8	5 3/8	2500	16,750	1100
	Standard Reflector		14493-1	\$	75PAR38/HAL/SP10	130	12	Spot 10°	C, CC-8	5 3/8	2500	14,000	1100
			14494-9	\$	75PAR38/HAL/FL25	130	12	Flood 25°	C, CC-8	5 3/8	2500	4350	1100
90	PAR-38	Med.Skt.	23650-5	\$	90PAR38/HAL/SP10	130	12	Spot 10°	C, CC-8	5 3/8	2500	16,400	1350
	Standard Reflector		23651-3	\$	90PAR38/HAL/FL25	130	12	Flood 25°	C, CC-8	5 3/8	2500	5350	1350
			14495-5	\$	90PAR38/HAL/WFL40	130	12	W. Flood 40°	C, CC-8	5 3/8	2500	2200	1350

For the most current product information, go to the e-catalog on www.philips.com
Halogen symbols and footnotes located on page 56