



Accent in style with multiple beam angles and improved lumens

PAR30 Indoor Flood LED

Philips PAR Dimmable LED Reflectors with high brightness LEDs are suited for track and recessed lighting. Energy saving, long life LED PAR long and short lamps install into existing fixtures, lower costs with reduced wattage and reduce re-lamping frequency.

Benefits

- Long life properties-- lowers maintenance costs by reducing re-lamp frequency
- Will not fade colors, avoids inventory spoilage
- Contains no mercury
- Emits virtually no UV/IR light in the beam
- 3-year or 5-year limited warranty depending upon operating hours

Features

- Dimmable* and non-dimmable versions available
- 45,000-hour rated average life⁺ for a 12W PAR30S
- Available in multiple beam angles: 10°, 15°, 22°, 25°, 36°
- Instant-on light
- Emits virtually no UV/IR light in the beam



Related products



13W, E26, PAR30L, Dimmable



11W/12W, E26, PAR30L



11W/12W/17W PAR30S/PAR38, Dimmable



12W, PAR30L, Dimmable



E26, PAR30S

Dimensional drawing

11PAR30S/END/F25 2700 DIM6/1

Product	C (Norm)	D (Norm)
LED 11W E26 2700K 120V PAR30S Dimmable	-	-
LED 11W E26 3000K 120V PAR30S Dimmable	-	-
LED 11W E26 4200K 120V PAR30S Dimmable	-	-
LED 11W E26 2700K 120V PAR30L Dimmable	-	-
LED 11W E26 3000K 120V PAR30L Dimmable	-	-
LED 11W E26 4200K 120V PAR30L Dimmable	-	-
LED 12W E26 3010K 120V PAR30S 10D Dimm	91	92
LED 12W E26 2790K 120V PAR30L 15D Dimm	113	92
LED 12W E26 3010K 120V PAR30L 15D Dimm	113	92
LED 12W E26 3030K 120V PAR30L 36D Dimm	113	92

Dimensional drawing

12PAR30S/END/F22 3000 DIM 6/1

Product	C (Norm)	D (Norm)
LED 12W WH 3030K 120V PAR30S Dimmable	-	-

12PAR30L/END/F22 2700 DIM 6/1

Product	C (Norm)	D (Norm)
LED 12W WW 2700K 120V PAR30L Dimmable	-	-
LED 12W WH 3030K 120V PAR30L Dimmable	-	-
LED 12W CW 4200K 120V PAR30L Dimmable	-	-

13PAR30L/END/F25 2700-800 DIM 6/1

Product	C (Norm)	D (Norm)
LED 13W 2700K 120V PAR30L 25D DIM	-	-

General Characteristics

Order code	Full product name	Cap-Base	Bulb	Rated Avg. Life (Hours)
929000202704	13PAR30L/END/F25 2700-800 DIM 6/1	E26	PAR30L	45000 hr
929000171502	11PAR30L/END/F22 2700 DIM 6/1	E26	PAR30L	40000 hr
929000171602	11PAR30L/END/F22 3000 DIM 6/1	E26	PAR30L	40000 hr
929000171702	11PAR30L/END/F22 4200 DIM 6/1	E26	PAR30L	40000 hr
929000192302	12PAR30L/END/S15 2700 DIM 6/1	E26	PAR30L	-
929000192402	12PAR30L/END/S15 3000 DIM 6/1	E26	PAR30L	45000 hr
929000193302	12PAR30L/END/F36 3000 DIM 6/1	E26	PAR30L	45000 hr
929000175602	12PAR30S/END/F22 3000 DIM 6/1	-	PAR30S	45000 hr

Order code	Full product name	Cap-Base	Bulb	Rated Avg. Life (Hours)
929000175802	12PAR30L/END/F22 2700 DIM 6/1	-	PAR30L	45000 hr
929000175902	12PAR30L/END/F22 3000 DIM 6/1	-	PAR30L	45000 hr
929000176002	12PAR30L/END/F22 4000 DIM 6/1	-	PAR30L	45000 hr
929000171202	11PAR30S/END/F25 2700 DIM6/1	E26	PAR30S	40000 hr
929000171302	11PAR30S/END/F22 3000 DIM 6/1	E26	PAR30S	40000 hr
929000171402	11PAR30L/END/F22 4200 DIM 6/1	E26	PAR30S	40000 hr
929000191202	13PAR30S/END/S10 3000 DIM 6/1	E26	PAR30S	45000 hr

Installation diagrams

E26

Light Technical Characteristics

Order code	Full product name	Color Code	Beam Angle	Approximate Lumens	Approx. MBCP	CRI
929000202704	13PAR30L/END/F25 2700-800 DIM 6/1	WW	25 D	820 Lm	3200 cd	80
929000171502	11PAR30L/END/F22 2700 DIM 6/1	WW	22 D	440 Lm	1880 cd	82
929000171602	11PAR30L/END/F22 3000 DIM 6/1	WH	22 D	440 Lm	1880 cd	85
929000171702	11PAR30L/END/F22 4200 DIM 6/1	CW	20 D	610 Lm	3100 cd	67
929000192302	12PAR30L/END/S15 2700 DIM 6/1	WW	15 D	-	5400 cd	84
929000192402	12PAR30L/END/S15 3000 DIM 6/1	WH	15 D	730 Lm	5800 cd	82

Order code	Full product name	Color Code	Beam Angle	Approximate Lumens	Approx. MBCP	CRI
929000193302	12PAR30L/END/F36 3000 DIM 6/1	WH	36 D	720 Lm	1300 cd	82
929000175602	12PAR30S/END/F22 3000 DIM 6/1	WH	22 D	705 Lm	3100 cd	-
929000175802	12PAR30L/END/F22 2700 DIM 6/1	WW	22 D	660 Lm	2900 cd	-
929000175902	12PAR30L/END/F22 3000 DIM 6/1	WH	22 D	725 Lm	3100 cd	-
929000176002	12PAR30L/END/F22 4000 DIM 6/1	CW	22 D	800 Lm	3600 cd	-

Order code	Full product name	Color Code	Beam Angle	Approximate Lumens	Approx. MBCP	CRI
929000171202	11PAR30S/END/F25 2700 DIM6/1	WW	22 D	455 Lm	1880 cd	82
929000171302	11PAR30S/END/F22 3000 DIM 6/1	WH	22 D	450 Lm	1880 cd	83
929000171402	11PAR30L/END/F22 4200 DIM 6/1	CW	20 D	610 Lm	3100 cd	65
929000191202	13PAR30S/END/S10 3000 DIM 6/1	WH	10 D	650 Lm	9000 cd	82

Electrical Characteristics

Order code	Full product name	Wattage	Voltage	Line Frequency
929000202704	13PAR30L/END/F25 2700-800 DIM 6/1	13 W	120 V	60 Hz
929000171502	11PAR30L/END/F22 2700 DIM 6/1	11 W	120 V	-
929000171602	11PAR30L/END/F22 3000 DIM 6/1	11 W	120 V	-
929000171702	11PAR30L/END/F22 4200 DIM 6/1	11 W	120 V	-

Order code	Full product name	Wattage	Voltage	Line Frequency
929000192302	12PAR30L/END/S15 2700 DIM 6/1	12 W	120 V	60 Hz
929000192402	12PAR30L/END/S15 3000 DIM 6/1	12 W	120 V	60 Hz
929000193302	12PAR30L/END/F36 3000 DIM 6/1	12 W	120 V	60 Hz
929000175602	12PAR30S/END/F22 3000 DIM 6/1	12 W	120 V	-
929000175802	12PAR30L/END/F22 2700 DIM 6/1	12 W	120 V	-
929000175902	12PAR30L/END/F22 3000 DIM 6/1	12 W	120 V	-
929000176002	12PAR30L/END/F22 4000 DIM 6/1	12 W	120 V	-
929000171202	11PAR30S/END/F25 2700 DIM6/1	11 W	120 V	-
929000171302	11PAR30S/END/F22 3000 DIM 6/1	11 W	120 V	-
929000171402	11PAR30L/END/F22 4200 DIM 6/1	11 W	120 V	-
929000191202	13PAR30S/END/S10 3000 DIM 6/1	12 W	120 V	60 Hz



© 2013 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2013, January 1
data subject to change