

[Return to search](#)[Print Page](#)

Product Number: 29508
Order Abbreviation: CF65EL/TWIST
General Description: Dulux EL 65W compact fluorescent lamp with integral 120V ballast, medium screw base, Color temperature 4100K, 82CRI

Product Information

Abbrev. With Packaging Info.	CF65ELTWIST 6/CS 1/SKU
Average Rated Life (hr)	8000
Base	Medium
Bulb	TWIST
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	4100
Diameter (in)	2.76
Diameter (mm)	70.1
Family Brand Name	Dulux® EL
Initial Lumens at 25C	4200
Mean Lumens at 25C	3360
Maximum Overall Length - MOL (in)	7.85
Maximum Overall Length - MOL (mm)	199.3
Nominal Wattage (W)	65.00

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature. .
- DULUX ELs meet CSA, FCC and UL requirements.

- Caution: DULUX EL units cannot be used on dimming circuits (unless the lamp is labeled dimmable), emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature for DULUX EL lamps is 0 degrees F
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

[Print Page](#)