

[Return to search](#)[Print Page](#)

**Product Number:** 58532  
**Order Abbreviation:** 20MR16/IR/NFL25/C 12V  
**General Description:** LOW VOLTAGE, ENERGY EFFICIENT 20 WATT NARROW FLOOD LAMP. SUITABLE FOR UNSHIELDED FIXTURES.

#### Product Information

Abbrev. With Packaging Info.	20MR16IRNFL25C 12V 20/CS 1/SKU
Average Rated Life (hr)	5000
Base	GU5.3 Bipin
Beam Angle (deg)	25
Beam Type	NFL
Bulb	MR16
Centerbeam Candlepower (cp)	2300
Class	C (gas)
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Filament	AXIAL
Horizontal Beam Angle (deg)	25
Lamp Finish	Covered
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	25

#### Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



#### Footnotes

- Infrared lamp technology
- Max. seal temperature 370 C (662F)

- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector and infrared reflective coating on the lamp capsule.
- Max pin temperature 220 C.
- Max temperature at lens reflector joint 240 C.

[Print Page](#)