



T10000R Series Pool & Spa Control Centers



The T10000R Series Control Centers feature an all-weather enclosure and contain one or two heavy duty timer mechanisms. In addition, they have provision to install switches or GFCI receptacle on the side and additional switches inside. The enclosure accepts any combinations of P1353ME or P4243ME or T100M or RC2000M or PF1000M Series mechanisms.

Applications

- Filter Pumps-Booster Pump Combinations
- Filter Pump-Light Controls
- Pool-Spa Combinations
- Yard Lighting
- Signs

Specifications

Case – 12" (30.5 cm) H x 12" (30.5 cm) W x 4-1/4" (10.8 cm) D, 0.048" steel with electrostatically applied light beige finish.

Knockouts – Five combination 1/2"-3/4" and two combination 3/4"-1" knockouts on the bottom.

One combination 1/2"-3/4" on the left side and one combination 3/4"-1" on the back.

One knockout 1-3/4" x 2-3/4" on the right side for mounting switches or GFCI.

Center Rating – 92 Amp per leg, 168 Amp Max. 120-240 VAC or 120-208 VAC single phase - 60 Hz

Time Switch Rating – 30 Amp Resistive Inductive, Tungsten or 1000 VA pilot duty each pole 120/208/240 VAC; 2 HP (24 FLA) - 120 VAC; 5 HP (28 FLA) - 240 VAC

Shipping Weight – See Table.

Agency Approval – CSA/C-US

Model #	Description/Mechanism	Switch	Clock Supply Volts 60 Hz	Shipping Weight
T10000R	Enclosure Only	None	NA / NA	9.3 lbs (4.2 kg)
T10101R	Two T101M	SPST – SPST	120 /120	11.0 lbs (5.0 kg)
T10004R	One T104M	NA – DPST	NA / 240	10.5 lbs (4.7 kg)
T10404R	Two T104M	DPST – DPST	240 / 240	11.0 lbs (5.0 kg)
T10604R*	T106M & T104M	SPDT – DPST	240 / 240	11.0 lbs (5.0 kg)
T12404R**	T104M201 & T104M	DPST –DPST	240 / 240	11.0 lbs (5.0 kg)

* For 2 speed pump applications.

** The heater protection switch (fireman switch) is closed when the time switch contacts are open to allow remote operation of the heater. A flow or pressure switch therefore must always be part of the heater control circuit.

For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A.

For additional "OFF" trippers (25 "OFF" per pack), order No. PA115.

For Stand offs for décor knockouts (4 stand-offs per pack), order No. 21T156A.



T10000R



T10004R



T10404R