

# The Can-Fan series come equipped with the extremely reliable external rotor motors.

## 100% Speed Controllable • 5 year warranty



Can-Fan



CF1 November 2007

FAN MODEL	RPM	VOLTS	MAX WATTS	MAX AMPS	0"	.125"	.25"	.375"	.5"	.75"	1.0"	1.25"	1.5"	MAX PS.	DUCT DIA.	SONES
4"	2640	115	68	0.69	123	113	104	94	85	69	54	35	11	1.65	4"	4
4"HO	2600	115	78	1.15	155	145	135	125	114	94	74	53	24	1.73	4"	5.5
6"	2750	115	82	0.69	269	249	228	206	185	148	115	80	37	1.72	6"	6
6"HO	2940	115	138	1.15	392	371	348	324	301	260	230	179	139	2.08	6"	12
8"	2950	115	139	1.16	483	455	433	405	377	320	264	209	153	2.16	8"	10
8"HO	2950	115	283	2.36	722	684	647	610	573	498	442	324	316	3.2	8"	10.5
10"	2750	115	142	1.19	495	472	448	423	397	347	292	267	187	2.37	10"	10.5
10"HO	2760	115	283	2.36	761	734	701	665	629	568	505	435	368	3.14	10"	13.5
12"	2860	115	286	2.39	874	843	811	779	746	677	597	555	445	3.22	12"	15.5
12"HO	3130	115	365	3.04	975	948	921	892	864	808	751	692	633	3.44	12"	16

Performance shown is for installation type D - Ducted inlet, Ducted outlet. Speed (RPM) shown is nominal. Performance is based on actual speed of test. Performance ratings do not include the effects of appurtenances in the airstream. = Static Pressure in Inches W.G.

CF Group Inc. certifies that the Can-Fan® Series shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

