CR Series LED Downlights

Easy to Install with Unprecedented Payback

THE QUALITY YOU DEMAND WITH THE SAVINGS YOU DESERVE.



Inspired by Your Needs

Solutions that Deliver

The Cree® CR Series LED downlights make it easy to upgrade existing lighting to more energy efficient, longer lasting, high quality LED technology. Designed for commercial and residential retrofits, they install quickly and easily into 6", some 5" or 4" recessed housings. Available in multiple lumen packages and various color temperatures the CR Series is an ideal retrofit solution.



Quick and Simple Installation

Quickly and simply installs into new or existing recessed housings from Cree and other manufacturers. An entire kitchen can be converted to energy-efficient LED lighting in minutes.

For installation instructions and to view an installation video visit:

www.cree.com/lighting/CRSeriesDownlights

High Quality LED Light

With color temperatures including 2700K, 3000K, 3500K and 4000K and High CRI, the CR Series light quality is equal to incandescent and halogen, while using up to 87% less energy.

Efficient and Effective

The CR Series LED Downlights are commercial and residential ENERGY STAR[®] qualified, opening up opportunities for



customers to realize utility rebates and incentives.

Designed with up to 50,000 hour expected useful life, the CR Series LED downlights could last for decades with typical use^{*}.

CR Series LED lighting is twice as efficient as incumbent CFLs and contain no toxic mercury.

Instant-on and Fully Dimmable

Stop waiting for CFLs to "warm up". The CR Series LED downlights turn on instantly, to full brightness.

Continuous dimming down to 5% with most, standard incandescent dimmers**, makes the CR Series LED Downlights ideal for many applications.

Footnotes:





| Cree TrueWhite® T | echnology | Cree Full Definition Color Quality | | |
|---|---|------------------------------------|-----------------------------------|--|
| CR4-575L | CR6-625L CR6-800L | CR4-575L-FD | CR6-625L-FD | |
| 575 lumens, 9.5W, 120V | 625 lumens, 9.5W, 120V 800 lumens, 12W, 120V | 575 lumens, 9.5W, 120V | 625 lumens, 12.5W, 120V | |
| 90 CRI at 2700K, 3000K, 3500K, 4000K | 90 CRI at 2700K, 3000K, 3500K, 4000K | 83 CRI at 2700K | 83 CRI at 2700K | |
| Dimmable to 5% | Dimmable to 5% | Dimmable to 5% | Dimmable to 5% | |
| 50,000 hours | 50,000 hours | 25,000 hours | 35,000 hours | |
| Fits most 4" housings | Fits most 6" and some 5" housings | Fits most 4" housings | Fits most 6" and some 5" housings | |
| .9 Power Factor | .9 Power Factor | .9 Power Factor | .9 Power Factor | |
| Commercial Energy Star® | Commercial Energy Star® | Commercial Energy Star® | Commercial Energy Star® | |
| WARRANTY: 5 years | WARRANTY: 5 years | WARRANTY: 5 years | WARRANTY: 5 years | |

Cree® CR Series LED Downlights

Lighting Without Compromise

Choose award-winning Cree color quality, which delivers bright, beautiful light while providing significant energy savings compared to incumbent products. A true no-compromise solution that provides:

- EXCEPTIONAL LIGHT QUALITY
 Delivers superior color accuracy with beautiful light characteristics and
 consistent color temperature.
- EQUAL LIGHT OUTPUT USING LESS ENERGY Produces light output equal to incumbent products while saving consumers up to 85% in energy costs.

LOW MAINTENANCE

Designed to last up to 50,000 hours while maintaining color consistency over the life of the product.

• UNPRECEDENTED PAYBACK

With significantly lower energy costs and virtually no maintenance, payback is less than one year in many applications*

CREE 👙 Cree[®] TrueWhite[®] Technology TRUE WHITE The highest level of color quality in the portfolio. Highly efficient light designed to enhance the details of a physical space or product where first impressions set the tone. Color Red Lifetime Quality Content Color Visual (CRI) (R9) Consistency Acuity Best Best Best Best

FD ____

Cree[®] Full Definition

Color quality that meets the needs of many spaces and is superior to most incumbent lighting technologies.

Color Red Lifetime Quality Content Color Visual (CRI) (R9) Consistency Acuity Good Good Good Good

Footnote:

*Based on typical commercial usage of CR6 🍽 FD @ 9 hours per day and \$0.11 per kWh electric costs and virtually zero maintenance.

Anatomy of CR Series LED Downlights The Cree Difference



- 1. LAMP BASE: Available as Edison (E26) or GU24
- 2. INTEGRATED POWER SUPPLY AND DRIVER ELECTRONICS
- 3. FLIP CLIPS: Used for installation into 6-inch housings
- 4. CREE LED ARRAY
 - Cree TrueWhite Technology*
 - Cree[®] Full Definition Color Quality Technology**
- 5. ADVANCED OPTICAL DIFFUSING LENS
- 6. LIGHT MIXING CHAMBER

Accessory Information

SNAP-IN TRIMS (Only available for CR6[™])

Snap-in Trim Kits are available in four standard color options.



CT6A Silver Diffuse Finish Reflector



CT6AW Wheat Diffuse Finish Reflector



CT6AB Black Diffuse Finish Reflector



СТ6ВВ Flat Black Diffuse Finish Reflector



CT6 Installed

6" HOUSINGS (Only available for CR6[™], CR6[™] FD and LR6[™])

The CR6[™] downlights fit into a variety of housings from Cree and other manufacturers.



H6 Series Specification-Grade Housing



RC6 Series Commercial-Grade Housing



RR6 Series Retrofit Housing

6" MOUNTING KITS (Only available for CR6™, CR6™ FD and LR6™) The CR6[™] downlights fit into a variety of mounting kits for ceiling, pendant or wall mounting.



Ceiling Mounts



SC6-WM Wall Mounts



SC6-CM Cord Mounts

6" COMMERCIAL RETROFIT KITS (Only available for CR6™, CR6™ FD and LR6™)

A field-installable kit to transform the existing commercial-grade downlights into housings ready to accept the CR6[™] downlights.



C6-LSA Commercial 120V or 277V, Hard-Wire, "Pan" Adaptor Kit

C6 Commercial 120V, Edison Base, "Pan" Adaptor Kit

Ordering Information



REPLACES:

575L = 50W BR Incandescent 15W CFL 625L = 65W BR Incandescent 18W CFL 800L = 90W BR Incandescent 26W CFL

Cree TrueWhite®

Example: CR6-575L-27K-120V-E26

| SERIES | SIZE | LUMENS | ССТ | VOLTAGE/ BASE | BASE TYPE | OPTIONS |
|---------|--|--|--|-------------------------|---|--------------------------------|
| CR | 4 = 4 inch 6 = 6 inch | 575L = 575 Lumens 625L = 625 Lumens** 800L = 800 Lumens** | 27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K | 120V - 120 Volts | E26 - Edison Base GU24 - GU24 Base (Title 24 Compliant) | D = Specular Reflector* |
| CR4™ FI | | CR6™ FD | 5. | 125 | PLACES: | |
| | | 3.5" | | 575 | | ndescent 15W CEL |

Full Definition

5″ —

| SERIES | SIZE | LUMENS | ССТ | VOLTAGE/ BASE | BASE TYPE | LED TECHNOLOGY |
|--------|--|--|--------------------|------------------|---|-----------------------------|
| CR | 4 = 4 inch 6 = 6 inch | 575L = 575 Lumens 625L = 625 Lumens** | 27K - 2700K | 120V - 120 Volts | E26 - Edison Base GU24 - GU24 Base (Title 24 Compliant) | FD - Full Definition |

*Only available for 4 inch models

** Only available for 6 inch models

Ordering information is for reference only. Some product configurations are not available. Please consult spec sheets for specific product availability and for further details.

Extended Product Offering



LR Series

- Equivalent up to Twin 26W CFL
- 6" aperture with multiple reflector depths
- Efficacy up to 90 LPW
- Up to 1800 lumens at 20W
- Multiple CCTs at 90 CRI
- Dimmable to 5% (120V)
- Available in 120V only



LR4™

7.5" -

- Equivalent to 50W BR20 Incandescent
- 4" aperture with spun aluminum reflectors
- Efficacy up to 51 LPW
- Up to 540 lumens at 10.5W
- Multiple CCTs at 90 CRI
- Dimmable to 20%
- · Available in 120V only



LE6™

- Equivalent up to 32W Fluorescent
- 6" aperture with adjustable lens
- Efficacy up to 42 LPW
- Up to 500 lumens at 12W
- Multiple CCTs at 90 CRI
- Dimmable to 5% (120V)
- Available in 120V only

Example: CR6-575L-27K-120V-E26-FD

Cree IS LED Lighting.

Visit www.cree.com/lighting

or contact a Cree lighting representative to learn more.

© 2013 Cree, Inc. All rights reserved. For informational purposes only. See www.cree.com/lighting/products/ warranty for warranty terms. Cree*, the Cree logo, TrueWhite* and the Cree TrueWhite Technology logo are registered trademarks and CR4[™], CR6[™], LR4[™] and LE6[™] are trademarks of Cree, Inc. Commercial Energy Star* and the Energy Star logo are registered trademarks of the U.S. EPA. CAT/FLYR-C002 Rev. Date 06/20/2013

