

# UR Series

LED Upgrade Kit



## The Easiest Way to Break Through to LED Lighting.

### **SIMPLE** Installation

Retrofits existing fluorescent fixtures fast with unique magnetic design and quick connect technology.

### **PERFORMANCE-OPTIMIZED** Technology

Provides high-efficiency light up to 102 lumens per watt along with a remarkable 7-year limited warranty.

### **MAXIMUM** Versatility

Offering both 2' and 4' options along with multiple lamp combinations provides a fit for any application.

### **CODE-COMPLIANT** Applicability

Designed to meet typical footcandle requirements for office and commercial space.

# UR Series LED Upgrade Kit

The UR Series LED Upgrade Kit delivers enhanced spectrum 80 CRI light while achieving up to 102 lumens per watt. This innovative kit is designed to easily retrofit existing fixtures to energy-saving LED. The UR Series is available in neutral or cool color temperatures and step dimming comes standard. Its cost-effective, lightweight design and LED brilliance make the UR Series a fit for almost all applications where payback, price and quality are critical.

## COST SAVING UPGRADE

Targeted to deliver a shortened payback with low initial cost, the UR Series makes the switch to LED an easy one.

## EASE OF INSTALLATION

Designed from an installer's point of view, convert aging fluorescent fixtures quickly with magnetic clips that allow hands-free placement of LED lightbars and electrical quick connects for simple, error-free power connections.

## VENDOR-INDEPENDENT APPLICATION

Nearly all fluorescent fixtures are adaptable with the UR Series design flexibility of lightbars and driver technology. Additionally, the UR Series is designed to deliver light levels that meet the requirements of office and commercial spaces.

Product specifications subject to change at any time. Visit [www.cree.com/lighting](http://www.cree.com/lighting) to find the most up-to-date information and for recommended dimming control options.

## PERFORMANCE SUMMARY

### Upgrade Existing Fixtures

**Efficacy:** Up to 102 LPW at source level

**Input Power:** 4' - 44 watts / 2' - 36 watts

**4' Kit:** Delivered System Light Output: 4500 lumens  
Expected Fixture Light Output: 4000 lumens\*

**2' Kit:** Delivered System Light Output: 3600 lumens  
Expected Fixture Light Output: 3200 lumens\*

**CRI:** >80

**CCT:** 3500K, 4000K

**Input Voltage:** 120-277 VAC

**Limited Warranty:** 7 years

**Lifetime:** Designed to last 50,000 hours

**Controls:** Step Level to 50%

**Mounting:** Existing Recessed

\* Varies by Fixture

## UR2-24™ / UR3-24™

- (2 or 3) 2' Lightbars
- (4) or (6) Mounting Clips
- (8) or (12) Self-Tapping Screws
- (1) LED Driver
- (1) Installation Instructions
- (1) UL1598C Certification Label

UR2-24™

## UR2-48™ / UR3-48™

- (2 or 3) 4' Lightbars
- (6) or (9) Mounting Clips
- (8) or (12) Self-Tapping Screws
- (1) LED Driver
- (1) Installation Instructions
- (1) UL1598C Certification Label

UR2-48™

