

## PRODUCT SPECIFICATION SHEET

**Model #: 80227**

**Description: DB2S2232RS120N**

Line Voltage: 120V 60Hz

Rapid Start

Series Lamp Operation

Normal Power Factor Correction

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF	BLE
Type	No.	Watts										
FC12T9	1+1	32	32 F/0°C	120	0.58	40	150	0.50	1.7	0.72	1.80	N/A
FC8T9		22										

**Performance**

Meets ANSI Standard C82.11-2005

Meets ANSI Standard C62.41-2002

Meets FCC Part 18 consumer limits

**Safety**

No PCB's, Type HL

UL & cUL listed (Class P, Type I Outdoor)

OCV 300V

**Application**

Remote Mounting: 18ft. max. Lead length, 18AWG

Maximum Ambient Temperature: 167 F, 75°C

Sound Rated: A

**Physical Parameters**

Length 6.0"

Width 1.7"

Height 1.1"

Mounting 5.75"

Weight 0.79lbs

**Lead Length**

White, Black 14" (±1")

Yellow 8" (±1")

Blue, Red 8" (±1")

