

PRODUCT SPECIFICATION SHEET

Model #: 80228

Description: DB2S3240RS120N

- LineVoltage:120V60Hz
- SeriesLamp Operation
- Rapid Start
- NormalPowerFactor Correction

LampType			Min.Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF	BLE
Type	No.	Watts										
FC16T9	1+1	40	32 ℱ/0°C	120	0.84	58	150	0.50	1.7	0.77	1.33	N/A
FC12T9		32										

Performance

- MeetsANSIStandardC82.11-2005
- MeetsANSIStandardC62.41-2002
- Meets FCCPart18Consumerlimits

Safety

- NoPCB's,Type HL
- UL&cULlisted(Class P,Type 1Outdoor)
- OCV300V

Application

- Remote Mounting: 18ft.max.Leadlength, 18AWG
- MaximumAmbientTemperature: 167 ℱ/75°C
- SoundRated: A

PhysicalParameters

- Length 6.0"
- Width 1.7"
- Height 1.1"
- Mounting 5.75"
- Weight 0.79lbs

LeadLength

- White, Black 14"(±1")
- Yellow 8"(±1")
- Blue,Red 8"(±1")

