

Model Number:

Type:

Job:

Approvals:

STANDARD FEATURES

- Housing constructed of 20 gauge galvanized steel
- Red or green high intensity LEDs
- Constant uniform illumination
- Minimum of 129 LEDs spelling for word "EXIT", 7 LEDs for each arrow
- 1/8" protective polycarbonate shield
- White or Black enclosure colors
- Optional enclosure colors available
- Chevron style universal arrow
- Reusable arrow covers
- 120/277V dual primary 60Hz input
- Short circuit protection
- Voltage surge protection
- 25 year warranty
- 5 year pro-rated warranty on battery

BATTERY BACK-UP

- Automatic diagnostic tester available
- Trickle charge circuitry for extended battery life
- Overcharge protection provided by zener diode
- Test button located on bottom for easy testing
- LED AC/DC indicators located on exit face protected by polycarbonate shield
- Flasher/buzzer options meet ADA regulations
- Low voltage disconnect eliminates deep discharge
- Brown-out protection
- ETL recognized maintenance-free lead acid battery
- ETL listed 90 minute emergency run time, 24 hour recharge time
- EL option available



Shown: 502-LB-WH


EL2A

The 500 Series is the brightest most visible sign in the industry in both normal and smoke-filled environments. Constructed of durable 20 gauge steel. The 500 Series direct view exit provides bright illumination with individual LEDs spelling the word EXIT.

DIMENSIONS

Height: 8½" • Width: 12¾" • Depth: 3¾"

MOUNTING CANOPY DIMENSIONS



WARRANTY

Any component that fails due to manufacturer's defect is guaranteed for 25 years with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or acts of God.

CONFORMANCE TO CODES & STANDARDS

ETL listed. Meets UL 924, NFPA 101 (Life Safety Code) NEC, OSHA and Energy Star illumination standards.



SPECIFICATIONS ARE SUBJECT
TO CHANGE WITHOUT NOTICE

ENERGY EFFICIENT

Starting at only 4 watts, the Exitronix 500 series will save up to 95% of energy costs over conventional bulb signs.

CONSTRUCTION

Enclosure, cover, face plate, and mounting canopy are 20 gauge galvanized steel with baked-on, powder coated paint. Face plate has 3/4" black letters with red or green LEDs. 1/8" polycarbonate shield protects LEDs from impact. *Optional face plates are available.

MAINTENANCE-FREE

NEVER CHANGE ANOTHER BULB!!! LEDs (Light Emitted Diodes) are rated for 1.7 million hours (194 years) without failure, cutting replacement costs 100% over conventional bulb signs.

INSTALLATION

Installs in minutes with easy-to-read instructions and detailed diagrams. No special hardware or tools necessary. Internally housed components and battery eliminate the use of a canopy when back mounting single faced exits. Mounting canopy included.

AUTOMATIC DIAGNOSTIC TESTER

This multifunctional option automatically analyzes the operating condition of the sign every seventh day and provides a visual warning if failure has occurred.

EMERGENCY LIGHTS

Emergency lights are single or double face compatible with field selective top or side mounting. Choice of 1 or 2 lights with each utilizing a 6 volt, 5.4 watt high intensity incandescent lamp. Flashing LED display in emergency mode is standard with emergency lights.

ORDERING INFORMATION:

502		WB		WH		AT		TRH		A	
SERIES		POWER SOURCE		ENCLOSURE COLOR		OPTIONS		OPTIONAL HARDWARE		EL OPTION	
502=	Red Single Face	LB =	Less Battery	WH=	White	AT=	Automatic Diagnostic Tester	TRH=	Tamper Resistant Hardware	EL2A=	Par 36 White Thermoplastic
503=	Red Double Face	WB =	With Battery	BL=	Black	DL=	LED Down Light	TRT6=	Tamper Resistant Tool	EL2B=	Par 36 Black Thermoplastic
G502=	Green Single Face	NC =	Ni Cad*	CC=	Custom Color (Please specify)	FL=	Flasher	ER1/Kit=	1' Pendant Kit	EL2C=	Par 18 White Thermoplastic
G503=	Green Double Face	* Not Available with EL option				BZ=	Audible Alarm	ER2/Kit=	2' Pendant Kit	EL2D=	Par 18 Black Thermoplastic
						FB=	Flasher & Audible Alarm	E12=	12" Pendant Extension	EL2E=	Par 36 Brushed Aluminum
						A1=	Fire Alarm Interface w /Flasher	E24=	24" Pendant Extension	EL2F=	Par 36 White Aluminum
						A2=	Fire Alarm Interface w / Flasher & Audible Alarm			EL2G=	Par 36 Black Aluminum
						DR=	Damp Location Rating			EL0=	18 Watts of Remote Capacity (No Lamps)
						6V=	6 Volt DC Remote Emergency Power				
						12V=	12 Volt DC Remote Emergency Power				
						2CI=	Two AC Circuit Inputs				
						C*=	Custom Color Faceplates (See Chart)				
						MR1=	1" Remote Steel Unit				
						MR2=	Remote Twin Unit				
						TF =	10 hour run time with Flasher / 5 hours continuous				

CUSTOM COLOR FACEPLATES

Designator	Description
C1	Brushed Chrome Face w/Green Letters
C2	Black Face w/Chrome Letters
C3	Black Face w/Red Letters
C4	Black Face w/Green Letters
C5	Red Face w/White Letters
C6	White Face w/Red Letters
C7	Green Face w/White Letters
C8	Black Face w/White Letters
C9	Brushed Chrome Face w/Black Letters
C10	White Face w/Green Letters
C11	Brushed Brass Face w/Black Letters

YOUR LOCAL REPRESENTATIVE IS:

EXITRONIX™

A DIVISION OF THE

BARRON LIGHTING GROUP

1911 W. Parkside Lane • Phoenix, AZ 85027

(800) 533-3948 • Fax: (623) 580-8948

www.exitronix.com • www.barronltg.com