



COVERED DECORATIVE CFL

Decorative Candle and Candelabra CFL

Nominal Wattage	Overdrive Model #	Item Description & CCT	Initial Lumen	Average Rated Life (Hrs.)	Diameter (Inches/mm)	Length/ (Inches/mm)	Pack Inner/ Master	Item #
7	7WODCD/E12	7W Candle CFL Candelabra Base Soft White	340	10,000	1.8 / 45	4.7 / 119	12	139
7	7WODCD	7W Candle CFL Medium Base Soft White	340	10,000	1.8 / 45	4.8 / 122	12	140

Globe CFL

9	9W/ODGS	9W G25 Globe Spiral - CFL - Soft White	500	10,000	3.1 / 79	4.4 / 110	12	036
15	● 15W/ODGS	15W G27 Globe Spiral - CFL - Soft White	820	10,000	3.4 / 87	4.7 / 120	12	131

Covered A shape CFL

7	● 7W/ODA	7W A17 Type spiral CFL-Soft White	450	10,000	2.1 / 54	4.3 / 108	12	077
15	● 15W/ODA	15W A21 Type spiral CFL-Soft White	800	10,000	2.6 / 67	5.4 / 137	12	125

Applications




WALL SCONE



CHANDELIER



CEILING FAN



READING LAMP



OUTDOOR COVERED

Features

- 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact in Size and fits most applications

Notes

- Not Dimmable
- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance

