

14311 - Q350T3/CL/HIR

GE Watt-Miser® T2.5

a product of ecomagination Energy Savings





CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Risk of Fire
- Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Operate lamp only in specified position -- see instructions.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament

Bulb Finish

Rated Life (NOM)

Halogen - Double-Ended T2.5 Recessed Single Contact (R7s) C-8 Clear 2000.0 h

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)9600.0Color Temperature (NOM)3000.0 KNominal Initial Lumens per Watt27.42857(NOM)27.42857

ELECTRICAL CHARACTERISTICS

Wattage (NOM) Voltage (NOM) Burn Position 350.0 130.0 Horizontal

DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM) 4.688 in(119.1 mm) 0.312 in(7.9 mm) 2.250 in(57.2 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168143110