



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > [Compact Fluorescent](#) > [Self-Ballasted](#) > [Spiral®](#) > [T3](#) > 15829**15829 – FLE10HT3/2/827**

GE Soft White Spiral® T3 - Facilities; Retail Display; Hospitality; Office; Restaurant



- Up to 75% energy savings One piece unit screws directly into incandescent sockets T3 Spirals® lamps provide economical solution with small overall size

 a product of
ecomagination™


- High Color Rendering
- cUL Listed
- Energy Savings
- UL Listed


**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	T3
Base	Medium Screw (E26)
ENERGY STAR® Qualified	Yes
Wattage	10
Voltage	120
Rated Life	8000 hrs
Starting Temperature (MIN)	-15 °C (5 °F)
Total Harmonic Distortion (THD)	120 %
Picograms of Mercury	1042 picograms
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

Bulb



Base



Package

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)**Brochures**

Product Brochures

- [Compact Fluorescent Lamps](#)
- [GE Consumer & Industrial ENERGY STAR® Program](#)

[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	520
Mean Lumens	420
Nominal Initial Lumens per Watt	52
Color Temperature	2700 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
Input Current	0.1400 A
Power Factor	0.6

DIMENSIONS

Maximum Overall Length (MOL)	4.4000 in (111.7 mm)
Nominal Length	4.400 in (111.7 mm)

PRODUCT INFORMATION

Product Code	15829
Description	FLE10HT3/2/827
Standard Package	Case
Standard Package GTIN	10043168158296
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168158299

 CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

[Return To Top](#)

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
 Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2008