



Commercial Products & Solutions


 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > [Sealed Beam](#) > [PAR](#) > [PAR36](#) > 19877
19877 – 35PAR36/H/FL30

GE PAR36 - Wide Flood

- Standard Halogen - Crisp, white light

[Print this Page](#)
[Convert to PDF](#)
GENERAL CHARACTERISTICS

Lamp type	Sealed Beam - PAR
Bulb	PAR36
Base	Screw Terminals
Filament	C-6
Product Technology	Halogen
Wattage	35
Voltage	12
Voltage (MIN)	35
Rated Life	4000 hrs
Rated Life (Vert)	4000 hrs
Primary Application	Wide Flood



Bulb



Base



Filament

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	250
Initial Lumens (Hor)	7.142857
Initial Lumens (Vert)	250
Beam Spread - Horizontal	40° - 10 %
Beam Spread - Vertical	34° - 10 %
Center Beam Candlepower (CBCP)	900
Color Temperature	3050 K
Max. Beam Candlepower (MBCP) (MAX)	900
Nominal Initial Lumens per Watt	7

DIMENSIONS

Maximum Overall Length (MOL)	2.7500 in (69.8 mm)
Bulb Diameter (DIA)	4.500 in (114.3 mm)

PRODUCT INFORMATION

Product Code	19877
Description	35PAR36/H/FL30
Standard Package	Case
Standard Package GTIN	00043168198776
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1

ADDITIONAL RESOURCES[Catalogs](#)**Brochures**

Product Brochures

- [Halogen Lamps](#)

[IES/Photometric Download](#)[Disposal Policies & Recycling Information](#)

No Of Items Per Standard Package 12

UPC 043168970297

 **CAUTIONS & WARNINGS**

[See list of cautions & warnings.](#)

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Careers](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright 2010 General Electric Company