


# 23719 - Q250PAR/SP10

GE Quartzline® PAR38 - Narrow Spot

# DIA.





### **CAUTIONS & WARNINGS**

### Caution

Risk of Burn

- Allow lamp to cool before handling.
- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

### Warning

- Electric Shock
- Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Avoid direct water/liquid contact.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.

### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Rated Life Primary Application Sealed Beam - PAR PAR38 Medium Skirt (E26/50x39) CC-8 4200.0 hrs Narrow Spot

### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens 3600.0 Center Beam Candlepower 40000.0 (CBCP) Color Temperature 2880.0 K Max. Beam Candlepower 40000.0 (MBCP) (MAX) Nominal Initial Lumens per Watt 14

## **ELECTRICAL CHARACTERISTICS**

Wattage	250.0
Voltage (MIN)	250.0
Voltage	120.0

# DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) 5.3100 in(134.9 mm)

4.750 in(120.6 mm)

### **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168237192