



WORLDWIDE PARTNER

Commercial Products & Solutions

SITE SEARCH > HOME * PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS

Where to Buy | FAQs | Contact Us | EliteNet

Products > 25186

25186 - FLE20HT3/2/841

GE Spiral® T3 - Facilities; Retail Display; Hospitality; Office; Restaurant







High Color Rendering cUL Listed Energy Savings

UL Listed

GENERAL CHARACTERISTICS

Lamp type	Compact Fluorescent - Self- Ballasted
Bulb	T3
Base	Medium Screw (E26)
ENERGY STAR® Qualified	Yes
Wattage	20
Equivalent Wattage	75 W
Rated Life	8000 hrs
Starting Temperature (MIN)	-15 ℃ (5 ℉)
Picograms of Mercury	648 picograms
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	965
Nominal Initial Lumens per Watt	48
Color Temperature	4100 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
Input Current	0.3000 A

DIMENSIONS

Maximum Overall Length (MOL)	4.7000 in (119.3 mm)
Nominal Length	4.700 in (119.3 mm)

PRODUCT INFORMATION

Description FL F20LIT2/2/044	Product Code	25186
Description FLE20F13/2/841	Description	FLE20HT3/2/841







View Larger

ADDITIONAL RESOURCES

<u>Catalogs</u>

Testimonials

Brochures

Product Brochures

- Compact Fluorescent Lamps
- GE Consumer & Industrial ENERGY STAR®
 Program

Disposal Policies & Recycling Information

Ctondord Doolsons	Casa
Standard Package	Case
Standard Package GTIN	10043168251867
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168251860

A CAUTIONS & WARNINGS

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use Copyright General Electric Company 1997-2008