


29696 - CMH39T/U/942/G12

GE ConstantColor® PulseArc® CMH® Ceramic Metal Halide T4.5



CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

- Lamp may shatter and cause injury if broken
 - Do not use excessive force when installing lamp.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- A damaged lamp emits UV radiation which may cause eye/skin injury
 - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- Risk of Electric Shock
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use beyond rated life.
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Operate lamp only in specified position.
 - Use in enclosed fixture rated for this product.
 - Use only properly rated ballast.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use fused or thermally protected ballast - see instructions.
 - Use in fixture rated for this product.

NOTES

- Rated life is 15,000 hours on magnetic ballasts.

GENERAL CHARACTERISTICS

| | |
|---------------------------|-------------------------------------------------|
| Lamp Type | High Intensity Discharge - Ceramic Metal Halide |
| Bulb | T4.5 |
| Base | Bi-Pin (G12) |
| Wattage | 39 |
| Rated Life | 18000 hrs |
| Bulb Material | Quartz |
| Lamp Enclosure Type (LET) | Enclosed fixtures only |
| LEED-EB MR Credit | 99 picograms Hg per mean lumen hour |
| Additional Info | UV control |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------|--------|
| Initial Lumens | 3200 |
| Mean Lumens | 2600 |
| Nominal Initial Lumens per Watt | 82 |
| Color Temperature | 4000 K |
| Color Rendering Index (CRI) | 88 |

ELECTRICAL CHARACTERISTICS

| | |
|-------------------------------|----------------------------|
| Burn Position | Universal burning position |
| Warm Up Time to 90% (MAX) | 2 min |
| Hot Restart Time to 90% (MAX) | 7 min |

DIMENSIONS

| | |
|------------------------------|---------|
| Maximum Overall Length (MOL) | 3.56 cm |
| Light Center Length (LCL) | 2.18 cm |

PRODUCT INFORMATION

| | |
|----------------------------|------------------|
| Product Code | 29696 |
| Description | CMH39T/U/942/G12 |
| ANSI Code | C130/M130 |
| Standard Package | Case |
| Standard Package GTIN | 10043168296967 |
| Standard Package Quantity | 12 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard | 12 |
| Package | |
| UPC | 043168296960 |